

Package ‘GmicR’

November 27, 2024

Type Package

Title Combines WGCNA and xCell readouts with bayesian network learning to generate a Gene-Module Immune-Cell network (GMIC)

Version 1.21.0

Author Richard Virgen-Slane

Maintainer Richard Virgen-Slane <RVS.BioTools@gmail.com>

Description This package uses bayesian network learning to detect relationships between Gene Modules detected by WGCNA and immune cell signatures defined by xCell. It is a hypothesis generating tool.

License GPL-2 + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

Imports AnnotationDbi, ape, bnlearn, Category, DT, doParallel, foreach, gRbase, GSEABase, gRain, GOstats, org.Hs.eg.db, org.Mm.eg.db, shiny, WGCNA, data.table, grDevices, graphics, reshape2, stats, utils

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

StagedInstall yes

biocViews Software, SystemsBiology, GraphAndNetwork, Network, NetworkInference, GUI, ImmunoOncology, GeneExpression, QualityControl, Bayesian, Clustering

git_url <https://git.bioconductor.org/packages/GmicR>

git_branch devel

git_last_commit 84bfd05

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-11-26

Contents

| | |
|---------------------------|-----------|
| Auto_WGCNA | 2 |
| Batch_Net | 4 |
| bn_tabu_gen | 4 |
| Data_Prep | 6 |
| Gmic_viz | 7 |
| GO_Module_NameR | 8 |
| GSEAGO_Builder | 8 |
| InverseARCs | 9 |
| Query_Prep | 10 |
| xCell_loader | 11 |
| Index | 12 |

| | |
|------------|-------------------------------------------------------------------|
| Auto_WGCNA | <i>Carries out WGCNA with default settings or custom settings</i> |
|------------|-------------------------------------------------------------------|

Description

Carries out WGCNA with default settings or custom settings

Usage

```
Auto_WGCNA(
  datExpr,
  colname_correct = TRUE,
  minModuleSize = 10,
  deepSplit = 4,
  networkType = "signed hybrid",
  TOMType = "unsigned",
  corFnc = "bicor",
  mergeCutHeight = 0.25,
  sft_RsquaredCut = 0.85,
  removeFirst = FALSE,
  reassignThreshold = 1e-06,
  maxBlockSize = 25000,
  nThreads = NULL
)
```

Arguments

| | |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| datExpr | Expression data. A matrix (preferred) or data frame in which columns are genes and rows are samples. NAs are allowed, but not too many. See checkMissingData below and details. |
| colname_correct | a logical value. If TRUE (default), "." in gene names will be replaced with "-". This corrects a name change that is induced by R when creating a data.frame. If FALSE, no changes will be made. |

| | |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>minModuleSize</code> | minimum module size for module detection. See cutreeDynamic for more details. |
| <code>deepSplit</code> | integer value between 0 and 4. Provides a simplified control over how sensitive module detection should be to module splitting, with 0 least and 4 most sensitive. See cutreeDynamic for more details. |
| <code>networkType</code> | network type. Allowed values are (unique abbreviations of) "unsigned", "signed", "signed hybrid". See adjacency . |
| <code>TOMType</code> | one of "none", "unsigned", "signed". If "none", adjacency will be used for clustering. If "unsigned", the standard TOM will be used (more generally, TOM function will receive the adjacency as input). If "signed", TOM will keep track of the sign of correlations between neighbors. |
| <code>corFnc</code> | the correlation function to be used in adjacency calculation. |
| <code>mergeCutHeight</code> | dendrogram cut height for module merging. |
| <code>sft_RsquaredCut</code> | desired minimum scale free topology fitting index R^2 . Default is 0.80. |
| <code>removeFirst</code> | should the first bin be removed from the connectivity histogram? |
| <code>reassignThreshold</code> | p-value ratio threshold for reassigning genes between modules. See Details. |
| <code>maxBlockSize</code> | integer giving maximum block size for module detection. Ignored if <code>blocks</code> above is non-NULL. Otherwise, if the number of genes in <code>datExpr</code> exceeds <code>maxBlockSize</code> , genes will be pre-clustered into blocks whose size should not exceed <code>maxBlockSize</code> . |
| <code>nThreads</code> | non-negative integer specifying the number of parallel threads to be used by certain parts of correlation calculations. This option only has an effect on systems on which a POSIX thread library is available (which currently includes Linux and Mac OSX, but excludes Windows). If zero, the number of online processors will be used if it can be determined dynamically, otherwise correlation calculations will use 2 threads. |

Value

Returns a lists containing network input parameters used for WGCNA, WGCNA module information, and quality control plots.

Note

This is a wrapper for WGCNA.

See Also

[blockwiseModules](#)

[adjacency](#)

Examples

```

sample_dat_dir<-system.file("extdata", "sample_dat.Rdata",
package = "GmicR", mustWork = TRUE)
load(sample_dat_dir)
GMIC_Builder<-Auto_WGCNA(sample_dat, mergeCutHeight = 0.35,
minModuleSize = 10)

```

Batch_Net

Generates a subgraph from query nodes

Description

Generates a subgraph from query nodes

Usage

```
Batch_Net(bn_output, Node_ids, relationship_type = "nbr")
```

Arguments

bn_output R object output from bn_tabu_gen function

Node_ids vector containing the nodes for subgraph generation.

relationship_type
the relationship to be returned for the specified query nodes. The options are "mb", "nbr", "parents", "children". Default setting is "nbr".

Value

a subgraph containing the selected nodes and relationships.

bn_tabu_gen

Uses tabu search algorithm to learn the structure of discretized data.

Description

Uses tabu search algorithm to learn the structure of discretized data.

Usage

```
bn_tabu_gen(
  Auto_WGCNA_OUTPUT,
  whitelist = NULL,
  blacklist = NULL,
  score = "bde",
  tabu = 50,
  iss = 10,
  cluster = NULL,
  debug = TRUE,
  bootstraps_replicates = 500
)
```

Arguments

| | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auto_WGCNA_OUTPUT | an R object generated by Auto_WGCNA and discretized using the Data_Prep function. |
| whitelist | a data frame with two columns (optionally labeled "from" and "to"), containing a set of arcs to be included in the graph. |
| blacklist | a data frame with two columns (optionally labeled "from" and "to"), containing a set of arcs not to be included in the graph. |
| score | character string indicating the score used for structure learning. If "bde" (default), prior is set to "uniform". If bds is used, the prior is set to "marginal". |
| tabu | a positive integer number, the length of the tabu list used in the tabu function. |
| iss | the imaginary sample size, used by the Bayesian Dirichlet scores (bde and bds) It is also known as "equivalent sample size". The default value is equal to 10. |
| cluster | an optional cluster object from package parallel . |
| debug | a boolean value. If TRUE a lot of debugging output is printed; otherwise the function is completely silent. |
| bootstraps_replicates | an integer for the number of bootstraps_replicates used for structure learning. Default value is 500 |

Value

The learned bayesian network

See Also

[arc.strength](#)

[hc](#)

[score](#)

Examples

```

GMIC_Builder_disc_dir<-system.file("extdata", "GMIC_Builder_disc.Rdata",
package = "GmicR", mustWork = TRUE)
load(GMIC_Builder_disc_dir)

no_cores<-1
cl<-parallel::makeCluster(no_cores)

GMIC_net<-bn_tabu_gen(GMIC_Builder_disc,
cluster = cl,
bootstraps_replicates = 50, score = "bds")
parallel::stopCluster(cl)

```

| | |
|-----------|---------------------------------------------------------------------------------------|
| Data_Prep | <i>Discretizes biological assay data in preparation for bayesian network learning</i> |
|-----------|---------------------------------------------------------------------------------------|

Description

Discretizes biological assay data in preparation for bayesian network learning

Usage

```

Data_Prep(
  Auto_WGCNA_OUTPUT = NULL,
  Remove_ME0 = FALSE,
  Numeric_Pheno_scores = NULL,
  xCell_Signatures = NULL,
  ibreaks = 60
)

```

Arguments

| | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auto_WGCNA_OUTPUT | R object generated from Auto_WGCNA function. |
| Remove_ME0 | a logical value. If FALSE (default), ME0 is not removed. If TRUE the eigengene for module 0 is removed prior to analysis. |
| Numeric_Pheno_scores | a data.frame with rows indicating sample ID and columns representing additional phenotype data to be included in BN learning. If NULL (default) no data will be included. If provided, the data.frame will be merged with MEs and discretized into three levels. |
| xCell_Signatures | the name of the text file generated by xCell that contains the cell signature scores. If NULL (default) the only module eigenegnes will be processed. If not NULL and if Auto_WGCNA_OUTPUT is NULL, cell signature scores will be discretized. |
| ibreaks | an integer that indicates the number of ibreaks used for discretization. The default value is 60. |

Value

a list containing a data.frame with module eigenegnes merged with Xcell signature scores and discretized into three levels: L, M, H. If Auto_WGCNA_OUTPUT is NULL, both scaled and discretized cell signatures will be return.

Note

Please verify that the sample name formatting is consistent between both datasets. Rownames in the module eigengenes data.frame and the column names of xCell signatures scores text file are matched for merging. Only samples that are present in both will be processed!

Examples

```
file_dir<-system.file("extdata", "IRIS_xCell_sig.txt",
package = "GmicR", mustWork = TRUE)
Disc_Xcell_sig<-Data_Prep(xCell_Signatures=file_dir, ibreaks = 10)
Disc_Xcell_sig$disc_data
```

Gmic_viz

Visualized network

Description

Visualized network

Usage

```
Gmic_viz(Auto_WGCNA_Output, Filter_unconnected_ME = TRUE)
```

Arguments

Auto_WGCNA_Output

R object with GMIC bayesian network

Filter_unconnected_ME

a logical value. If TRUE, the default, unconnected modules will be removed from the final network. If FALSE, all modules will be shown.

Value

a shiny object for network visualization.

Examples

```
GMIC_Final_dir<-system.file("extdata", "GMIC_Final.Rdata",
package = "GmicR", mustWork = TRUE)
load(GMIC_Final_dir)
if(interactive()){
Gmic_viz(GMIC_Final)}
```


Arguments

| | |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auto_WGCNA_OUTPUT | output from Auto_WGCNA function. |
| species | either 'Homo sapiens' (default) or 'Mus musculus'. |
| no_cores | Number of cores to use. Default = 4. |
| ontology | string either 'BP'(Biological Process; default), 'CC'(Cellular Component), or 'MF' (Molecular Function). |
| GO_conditional | A logical indicating whether the calculation should condition on the GO structure. will not be carried out. If TRUE, |
| colname_correct | a logical value. If TRUE (default), "." in gene names will be replaced with "-". This corrects a name change that is induced by R when creating a data.frame. If FALSE, no changes will be made. |

Value

Lists with gene ontology enrichment analysis, performed using GOSTats, for each module.

Note

gene names must be official gene symbol

Examples

```

GMIC_Builder_dir<-system.file("extdata", "GMIC_Builder.Rdata",
                             package = "GmicR", mustWork = TRUE)
load(GMIC_Builder_dir)
GMIC_Builder$GSEAGO_Builder_Output<-NULL
Test_GMIC_Builder<-GSEAGO_Builder(GMIC_Builder, no_cores = 1)
summary(Test_GMIC_Builder$GSEAGO_Builder_Output)

```

InverseARCs

Identifies arcs between nodes with inverse relationships

Description

Identifies arcs between nodes with inverse relationships

Usage

```
InverseARCs(Output, threshold = -0.3)
```

Arguments

| | |
|-----------|-------------------------------------------------------------------------------------------------|
| Output | a data frame containing the output of BN_Conditions function. |
| threshold | number indicating the maximum slope for defining negative relationships. Default level is -0.3. |

Value

arcs with inverse relationships

Examples

```
GMIC_net_dir<-system.file("extdata", "GMIC_net.Rdata",
package = "GmicR", mustWork = TRUE)
load(GMIC_net_dir)
GMIC_Final<-InverseARCs(GMIC_net, threshold = -0.3)
```

Query_Prep

Query Prep

Description

Query Prep

Usage

```
Query_Prep(
  Auto_WGCNA_OUTPUT,
  numGenes = 500,
  Find_hubs = FALSE,
  nThreads = NULL,
  calculate_intramodularConnectivity = TRUE
)
```

Arguments

| | |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auto_WGCNA_OUTPUT | R object generated by Auto_WGCNA function. |
| numGenes | integer indicating the number of random genes to test for hub gene detection. Default is 500. |
| Find_hubs | logical value. If TRUE, module hub genes will be returned. If FALSE (default), intramodularConnectivity will be returned without hub gene identification. |
| nThreads | non-negative integer specifying the number of parallel threads to be used by certain parts of correlation calculations. This option only has an effect on systems on which a POSIX thread library is available (which currently includes Linux and Mac OSX, but excludes Windows). If zero, the number of online processors will be used if it can be determined dynamically, otherwise correlation calculations will use 2 threads. |
| calculate_intramodularConnectivity | a logical value. If TRUE (default), the intramodularConnectivity will be calculated using the intramodularConnectivity function from WGCNA. If FALSE, a table of modules and genes will be returned without intramodularConnectivity values. |

Value

a data.frame detailing the gene symbols for each module. Gene intramodularConnectivity may also be returned. If detected, hub genes are annotated.

Examples

```
GMIC_Builder_dir<-system.file("extdata", "GMIC_Builder.Rdata",
package = "GmicR", mustWork = TRUE)
load(GMIC_Builder_dir)
GMIC_Builder<-Query_Prep(GMIC_Builder, Find_hubs = TRUE)
head(GMIC_Builder$Query)
```

| | |
|--------------|--------------------------------------------------------------------------------|
| xCell_loader | <i>Scales and centers data by sample/row in preparation for discretization</i> |
|--------------|--------------------------------------------------------------------------------|

Description

Scales and centers data by sample/row in preparation for discretization

Usage

```
xCell_loader(File = NULL)
```

Arguments

| | |
|------|---------------------------------------------------------------------------------------|
| File | the name of the text file generated by xCell that contains the cell signature scores. |
|------|---------------------------------------------------------------------------------------|

Value

xCell signatures scaled and centered by sample. For GMIC, ImmuneScore, StromaScore, and MicroenvironmentScore are removed.

Examples

```
file_dir<-system.file("extdata", "IRIS_xCell_sig.txt",
package = "GmicR", mustWork = TRUE)
Xcell_sig<-xCell_loader(file_dir)
plot(Xcell_sig$Bcells)
```

Index

adjacency, [3](#)
arc.strength, [5](#)
Auto_WGCNA, [2](#)

Batch_Net, [4](#)
blockwiseModules, [3](#)
bn_tabu_gen, [4](#)

cutreeDynamic, [3](#)

Data_Prep, [6](#)

Gmic_viz, [7](#)
GO_Module_NameR, [8](#)
GSEAGO_Builder, [8](#)

hc, [5](#)

InverseARCs, [9](#)

Query_Prep, [10](#)

score, [5](#)

xCell_loader, [11](#)