

Package ‘GenomAutomorphism’

November 29, 2024

Title Compute the automorphisms between DNA's Abelian group representations

Version 1.8.0

URL <https://github.com/genomaths/GenomAutomorphism>

BugReports <https://github.com/genomaths/GenomAutomorphism/issues>

Description This is a R package to compute the automorphisms between pairwise aligned DNA sequences represented as elements from a Genomic Abelian group. In a general scenario, from genomic regions till the whole genomes from a given population (from any species or close related species) can be algebraically represented as a direct sum of cyclic groups or more specifically Abelian p-groups. Basically, we propose the representation of multiple sequence alignments of length N bp as element of a finite Abelian group created by the direct sum of homocyclic Abelian group of prime-power order.

Depends R (>= 4.4.0),

License Artistic-2.0

Encoding UTF-8

biocViews MathematicalBiology, ComparativeGenomics, FunctionalGenomics, MultipleSequenceAlignment, WholeGenome

Imports Biostrings, BiocGenerics, BiocParallel, GenomeInfoDb, GenomicRanges, IRanges, matrixStats, XVector, dplyr, data.table, parallel, doParallel, foreach, methods, S4Vectors, stats, numbers, utils

RoxygenNote 7.3.1

Suggests spelling, rmarkdown, BiocStyle, testthat (>= 3.0.0), knitr

Roxygen list(markdown = TRUE)

Language en-US

LazyData false

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/GenomAutomorphism>

git_branch RELEASE_3_20

git_last_commit 708be70

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-28

Author Robersy Sanchez [aut, cre] (<<https://orcid.org/0000-0002-5246-1453>>)

Maintainer Robersy Sanchez <genomicmath@gmail.com>

Contents

aaindex1	3
aaindex2	4
aaindex3	5
aa_phychem_index	6
aln	7
aminoacid_dist	8
as.AutomorphismList	10
aut3D	11
autby_coef	13
autm	14
autm_3d	14
autm_z125	15
Automorphism-class	16
AutomorphismByCoef-class	16
AutomorphismByCoefList-class	17
automorphismByRanges	18
AutomorphismList-class	19
automorphisms	21
automorphism_bycoef	24
autZ125	25
autZ5	26
autZ64	28
base2codon	30
base2int	31
BaseGroup-class	33
BaseGroup_OR_CodonGroup-class	33
BaseSeq-class	34
BaseSeqMatrix-class	34
base_coord	34
base_repl	38
brca1_aln	38
brca1_aln2	39
brca1_autm	40
brca1_autm2	40
cdm_z64	41
CodonGroup-class	41
CodonMatrix-class	42
CodonSeq-class	43
codon_coord	44
codon_dist	46
codon_dist_matrix	48
codon_matrix	50

ConservedRegion-class	52
conserved_regions	52
covid_aln	54
covid_autm	55
cyc_aln	55
cyc_autm	56
dna_phyche	57
dna_phychem	58
GenomAutomorphism	59
getAutomorphisms	60
get_coord	61
get_mutscore	63
GRangesMatrixSeq-class	66
GRanges_OR_NULL-class	67
is.url	67
ListCodonMatrix-class	68
matrices	69
MatrixList-class	71
MatrixSeq-class	71
mod	72
modeq	73
modlineq	74
mut_type	75
peptide_phychem_index	76
reexports	78
seqranges	79
show,CodonSeq-method	81
slapply	82
sortByChromAndStart	83
str2chr	84
str2dig	85
translation	86
valid.Automorphism.mcols	87
valid.AutomorphismByCoef	88
valid.AutomorphismByCoefList	88
valid.AutomorphismList	89
valid.BaseGroup.elem	89
valid.CodonGroup.mcols	90
valid.MatrixList	90
[.AutomorphismList,ANY,ANY-method	91

Index**93**

aaindex1

List of 571 Amino Acid Physicochemical Indexes from AAindex Database

Description

The aminoacid indexes from Amino Acid Index Database <https://www.genome.jp/aaindex/> are provided here. AAindex (ver.9.2) is a database of numerical indices representing various physicochemical and biochemical properties of amino acids and pairs of amino acids.

Usage

```
data("aaindex1", package = "GenomAutomorphism")
```

Format

A list carrying the the description 566 Amino Acid Indices in AAindex ver.9.2 and the text file with the matrices imported from <https://www.genome.jp/aaindex/>.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[aaindex2](#) and [aaindex3](#).

Examples

```
## Load the mutation matrices from database from the packages
data("aaindex1", package = "GenomAutomorphism", envir = environment())

## Get the available aminoacid indices.
mat <- aa_phychem_index(aaindex = "aaindex1", acc_list = TRUE)
mat[1:10]
```

aaindex2

List of 94 Amino Acid Matrices from AAindex

Description

The aminoacid similarity matrices from Amino Acid Index Database <https://www.genome.jp/aaindex/> are provided here. AAindex (ver.9.2) is a database of numerical indices representing various physicochemical and biochemical properties of amino acids and pairs of amino acids.

Usage

```
data("aaindex2", package = "GenomAutomorphism")
```

Format

A list carrying the description of 94 Amino Acid Matrices in AAindex ver.9.2 and the text file of matrices imported from <https://www.genome.jp/aaindex/>.

Details

The similarity of amino acids can be represented numerically, expressed in terms of observed mutation rate or physicochemical properties. A similarity matrix, also called a mutation matrix, is a set of 210 numerical values, 20 diagonal and 20x19/2 off-diagonal elements, used for sequence alignments and similarity searches.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[aaindex2](#) and [aa_mutmat](#), and [get_mutscore](#).

Examples

```
## Load the mutation matrices from database from the packages
data("aaindex2", package = "GenomAutomorphism")

## Get the available matrices
mat <- aa_mutmat(aaindex = "aaindex2", acc_list = TRUE)
mat[1:10]
```

aaindex3

Statistical protein contact potentials matrices from AAindex ver.9.2

Description

A statistical potential (also knowledge-based potential, empirical potential, or residue contact potential) is an energy function derived from an analysis of known structures in the Protein Data Bank.

Usage

```
data("aaindex3", package = "GenomAutomorphism")
```

Format

A list carrying the the description 47 Amino Acid Matrices in AAindex ver.9.2 and the text file of matrices imported from <https://www.genome.jp/aaindex/>.

Details

A list of 47 amino acid matrices from Amino Acid Index Database <https://www.genome.jp/aaindex/> are provided here. AAindex is a database of numerical indices representing various physicochemical and biochemical properties of amino acids and pairs of amino acids.

The contact potential matrix of amino acids is a set of 210 numerical values, 20 diagonal and 20x19/2 off-diagonal elements, used for sequence alignments and similarity searches.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[aaindex1](#), [aaindex2](#), and [get_mutscore](#).

Examples

```
## Load the mutation matrices from database from the packages
data("aaindex3", package = "GenomAutomorphism")

## Get the available mutation matrices
mat <- aa_mutmat(aaindex = "aaindex3", acc_list = TRUE)
mat[1:10]
```

aa_phychem_index	<i>Amino acid mutation matrix</i>
------------------	-----------------------------------

Description

The aminoacid similarity matrices from Amino Acid Index Database <https://www.genome.jp/aaindex/> are provided here. **AAindex** (ver.9.2) is a database of numerical indices representing various physicochemical and biochemical properties of amino acids and pairs of amino acids.

The similarity of amino acids can be represented numerically, expressed in terms of observed mutation rate or physicochemical properties. A similarity matrix, also called a mutation matrix, is a set of 210 numerical values, 20 diagonal and 20x19/2 off-diagonal elements, used for sequence alignments and similarity searches.

Function **aa_phychem_index** is wrapper function to call two other functions: **aa_mutmat** and **aa_index**

Usage

```
aa_phychem_index(acc = NA, aaindex = NA, acc_list = FALSE, info = FALSE)

aa_mutmat(acc = NA, aaindex = c("aaindex2", "aaindex3"), acc_list = FALSE)

aa_index(acc = NA, acc_list = FALSE, info = FALSE)
```

Arguments

acc	Accession id for a specified mutation or contact potential matrix.
aaindex	Database where the requested accession id is locate. The possible values are: "aaindex2" or "aaindex3".
acc_list	Logical. If TRUE, then the list of available matrices ids and index names is returned.
info	Logical. if TRUE, then whole information for the physicochemical index will be returned.

Value

Depending on the user specifications, a mutation or contact potential matrix, a list of available matrices (indices) ids or index names can be returned. More specifically:

aa_mutmat: Returns an aminoacid mutation matrix or a statistical protein contact potentials matrix.

aa_index: Returns the specified aminoacid physicochemical indices.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[aaindex1](#), [aaindex2](#), [aaindex3](#), and [get_mutscore](#).

Examples

```
## Load the mutation matrices from database from the packages
data("aaindex1", "aaindex2", package = "GenomAutomorphism" )

## Get the available mutation matrices
mat <- aa_mutmat(aaindex = "aaindex2", acc_list = TRUE)
mat[seq(10)]

## Return the 'Base-substitution-protein-stability matrix
## (Miyazawa-Jernigan, 1993)'
aa_mutmat(acc = "MIYS930101", aaindex = "aaindex2")

## Return the 'BLOSUM80 substitution matrix (Henikoff-Henikoff, 1992)'
aa_mutmat(acc = "HENS920103", aaindex = "aaindex2")

## Using wrapping function
aa_phychem_index(acc = "EISD840101", aaindex = "aaindex1")

## Just the info. The information provided after the reference
## corresponds to the correlaiton of 'EISD840101' with other indices.
aa_phychem_index(acc = "EISD840101", aaindex = "aaindex1", info = TRUE)
```

aln

Simulated [DNAStringSet](#) class object

Description

This is a [DNAStringSet](#) carrying a small pairwise DNA sequence alignment to be used in the examples provided for the package functions.

Usage

```
data("aln", package = "GenomAutomorphism")
```

Format

[DNAStringSet](#) class object.

Examples

```
data("aln", package = "GenomAutomorphism")
aln
```

aminoacid_dist

*Distance Between Aminoacids in Terms of Codon Distance***Description**

This function computes the distance between aminoacids in terms of a statistic of the corresponding codons. The possible statistics are: 'mean', 'median', or some user defined function.

Usage

```
aminoacid_dist(aa1, aa2, ...)
```

```
## S4 method for signature 'character,character'
```

```
aminoacid_dist(
  aa1,
  aa2,
  weight = NULL,
  stat = c("mean", "median", "user_def"),
  genetic_code = "1",
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)
```

```
## S4 method for signature 'DNAStrngSet,ANY'
```

```
aminoacid_dist(
  aa1,
  weight = NULL,
  stat = c("mean", "median", "user_def"),
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)
```

```
## S4 method for signature 'AAStringSet,ANY'
```

```
aminoacid_dist(
  aa1,
  weight = NULL,
  stat = c("mean", "median", "user_def"),
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
```



```

    num.cores = 1L,
    tasks = 0L,
    verbose = FALSE
)

## S4 method for signature 'CodonGroup_OR_Automorphisms,ANY'
aminoacid_dist(
  aa1,
  weight = NULL,
  stat = c("mean", "median", "user_def"),
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)

```

Arguments

aa1, aa2	A character string of codon sequences, i.e., sequences of DNA base-triplets. If only 'x' argument is given, then it must be a DNAStringSet-class object.
...	Not in use yet.
weight	A numerical vector of weights to compute weighted Manhattan distance between codons. If <i>weight</i> = <i>NULL</i> , then <i>weight</i> = (1/4, 1, 1/16) for <i>group</i> = "Z4" and <i>weight</i> = (1/5, 1, 1/25) for <i>group</i> = "Z5" (see codon_dist).
stat	The name of some statistical function summarizing data like 'mean', 'median', or some user defined function ('user_def'). If <i>stat</i> = 'user_def', then function must have a logical argument named 'na.rm' addressed to remove missing (NA) data (see e.g., mean).
genetic_code	A single string that uniquely identifies the genetic code to extract. Should be one of the values in the id or name2 columns of GENETIC_CODE_TABLE .
group	A character string denoting the group representation for the given codon sequence as shown in reference (2-3).
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Only aminoacids sequences given in the following alphabet are accepted: "A", "R", "N", "D", "C", "Q", "E", "G", "H", "I", "L", "M", "F", "P", "S", "T", "W", "Y", "V", "", "-", and "X"; where symbols "" and "-" denote the presence a stop codon and of a gap, respectively, and letter "X" missing information, which are then taken as a gap.

The distance between any aminoacid and any of the non-aminoacid symbols is the ceiling of the greater distance found in the corresponding aminoacid distance matrix.

Value

A numerical vector with the pairwise distances between codons in sequences 'x' and 'y'.

References

1. Sanchez R. Evolutionary Analysis of DNA-Protein-Coding Regions Based on a Genetic Code Cube Metric. Curr. Top. Med. Chem. 2014;14: 407–417. <https://doi.org/10.2174/1568026613666131204110022>.
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152. [PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#).

See Also

[automorphisms](#) and [codon_coord](#)
[codon_dist](#)

Examples

```
## Write down to aminoacid sequences
x <- "A*LTHMC"
y <- "AAMTDM-"

aminoacid_dist(aa1 = x, aa2 = y)

## Let's create an AAStrngSet-class object
aa <- AAStrngSet(c(x, y))

aminoacid_dist(aa1 = aa)

## Let's select cube "GCAT" and group "Z5"
aminoacid_dist(aa1 = aa, group = "Z5", cube = "TCGA")
```

as.AutomorphismList *Methods for AutomorphismList-class Objects*

Description

Several methods are available to be applied on [Automorphism-class](#) and [AutomorphismList-class](#) objects.

Usage

```
as.AutomorphismList(x, grs = GRanges(), ...)

## S4 method for signature 'GRangesList,GRanges_OR_NULL'
as.AutomorphismList(x, grs = GRanges(), ...)

## S4 method for signature 'list,GRanges_OR_NULL'
as.AutomorphismList(x, grs = GRanges(), ...)
```

Arguments

`x` A [DataFrame](#) or a [automorphisms](#) class object.

`grs` A [GRanges-class](#) object.

`...` Not in use yet.

Value

The returned an AutomorphismList-class object.

See Also

[automorphism_bycoef](#), [automorphisms](#)

Examples

```
## Load a dataset
data("brca1_autm", package = "GenomAutomorphism")

## Let's transforming into a list of Automorphisms-class objects
x1 <- as.list(brca1_autm[seq(2)])

## Now, object 'x1' is transformed into a AutomorphismList-class object
as.AutomorphismList(x1)

## Alternatively, let's transform the list 'x1' into a GRangesList-class
## object.
x1 <- GRangesList(x1)

## Next, object 'x1' is transformed into a AutomorphismList-class object
as.AutomorphismList(x1)
```

aut3D

Compute the Automorphisms of Mutational Events Between two Codon Sequences Represented in Z_5^3 .

Description

Given two codon sequences represented in the Z_5^3 Abelian group, this function computes the automorphisms describing codon mutational events.

Usage

```
aut3D(
  seq = NULL,
  filepath = NULL,
  cube = c("ACGT", "TGCA"),
  cube_alt = c("CATG", "GTAC"),
  field = "GF5",
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  genetic_code = getGeneticCode("1"),
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

seq	An object from a DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences. The pairwise alignment provided in argument seq or the 'fasta' file filepath must correspond to codon sequences.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon & base</i> arguments are not provided.
cube, cube_alt	A character string denoting pairs of the 24 Genetic-code cubes, as given in references (2-3). That is, the base pairs from the given cubes must be complementary each other. Such a cube pair are call dual cubes and, as shown in reference (3), each pair integrates group.
field	A character string denoting the Galois field where the 3D automorphisms are estimated. This can be 'GF(4)' or 'GF(5)', but only 'GF(5)' is implemented so far.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
genetic_code	The named character vector returned by getGeneticCode or similar. The translation of codon into aminoacids is a valuable information useful for downstream statistical analysis. The standard genetic code is the default argument value applied in the translation of codons into aminoacids (see GENETIC_CODE_TABLE).
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Automorphisms in Z_5^{*3} are described as functions $f(x) = Ax \bmod Z_5$, where A is diagonal matrix, as noticed in reference (4).

Value

An object [Automorphism-class](#) with four columns on its metacolumn named: *seq1*, *seq2*, *autm*, and *cube*.

Author(s)

Roberly Sanchez (<https://genomaths.com>).

References

1. Sanchez R, Morgado E, Grau R. Gene algebra from a genetic code algebraic structure. J Math Biol. 2005 Oct;51(4):431-57. doi: 10.1007/s00285-005-0332-8. Epub 2005 Jul 13. PMID: 16012800. ([PDF](#)).
2. Roberly Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. <https://doi.org/10.1101/2021.06.01.446543>.
3. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152.[PDF](#).
4. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#).

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Automorphism on Z5^3
autms <- aut3D(seq = aln)
autms
```

autby_coef

Automorphisms between DNA Primate BRCA1 Genes Grouped by Coefficients

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the DNA sequences from the MSA of primate somatic cytochrome C grouped by automorphism's coefficients. The grouping derives from the dataset [brca1_autm](#) after applying function [automorphism_bycoef](#).

Usage

```
data("autby_coef", package = "GenomAutomorphism")
```

Format

[AutomorphismByCoefList](#) class object.

Examples

```
## Load the data set
data("autby_coef", package = "GenomAutomorphism")
autby_coef

## Mutation type found in the data
unique(autby_coef$human_1.human_2$mut_type)
```

autm	<i>Automorphisms between DNA Sequences from two COVID-19 genomes</i>
------	--

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the SARS coronavirus GZ02 (GenBank: AY390556.1: 265-13398_13398-21485) and Bat SARS-like coronavirus isolate bat-SL-CoVZC45 (GenBank: MG772933.1:265-1345513455-21542), nonstructural_polyprotein. The pairwise DNA sequence alignment is available in the dataset named [covid_aln](#) and the automorphisms were estimated with function [autZ64](#).

Usage

```
data("autm", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Details

The alignment of these DNA sequences is available at: <https://github.com/genomaths/seqalignments/raw/master/COVID-19> in the fasta file 'AY390556.1_265-13398_13398-21485_RNA-POL_SARS_COVI_GZ02.fas'

Examples

```
data("autm", package = "GenomAutomorphism")
autm
```

autm_3d	<i>Automorphisms between DNA Sequences from two COVID-19 genomes</i>
---------	--

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the SARS coronavirus GZ02 (GenBank: AY390556.1: 265-13398_13398-21485) and Bat SARS-like coronavirus isolate bat-SL-CoVZC45 (GenBank: MG772933.1:265-1345513455-21542), nonstructural_polyprotein. The pairwise DNA sequence alignment is available in the dataset named [covid_aln](#) and the automorphisms were estimated with function [aut3D](#).

Usage

```
data("autm_3d", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Examples

```
data("autm_3d", package = "GenomAutomorphism")
autm_3d
```

autm_z125

Automorphisms between DNA Sequences from two COVID-19 genomes

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the SARS coronavirus GZ02 (GenBank: AY390556.1: 265-13398_13398-21485) and Bat SARS-like coronavirus isolate bat-SL-CoVZC45 (GenBank: MG772933.1:265-1345513455-21542), nonstructural_polyprotein. The pairwise DNA sequence alignment is available in the dataset named [covid_aln](#) and the automorphisms were estimated with function [autZ125](#).

Usage

```
data("autm_z125", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Examples

```
data("autm_z125", package = "GenomAutomorphism")
autm_z125
```

Automorphism-class	<i>A class definition to store codon automorphisms in a given Abelian group representation.</i>
--------------------	---

Description

Two classes are involved in to storing codon automorphisms: **Automorphism-class** and **AutomorphismList-class**.

Details

An **Automorphism-class** object has six columns: "seq1", "seq2", "coord1", "coord2", "autm", and "cube". See the examples for function `automorphisms`. Observe that as the **Automorphism-class** inherits from **GRanges-class** the transformation starting from a **GRanges-class** object into an **Automorphism-class** is straightforward.

However, the transformation starting from a `data.frame` or a **DataFrame-class** object "x" requires for the creation of an additional **GRanges-class** object, which by default will have the argument `seqnames = "1"`, `strand = "+"`, `start/end = seq(row(x))`, `length = nrow(x)`. These details must be keep in mind to prevent fundamental errors in the downstream analyses.

Value

Given the slot values, it defines an Automorphism-class object.

Automorphism-class methods

as(from, "Automorphism")::

Permits the transformation of a `data.frame` or a **DataFrame-class** object into **Automorphism-class** object if the proper columns are provided.

Methods from **GRanges-class** can also be applied.

See Also

[AutomorphismByCoef-class](#) and [AutomorphismList-class](#)

AutomorphismByCoef-class	<i>A class definition to store conserved gene/genomic regions found in a MSA.</i>
--------------------------	---

Description

Objects from this class are generated by function `automorphism_bycoef`.

Value

AutomorphismByCoef-class definition.

AutomorphismByCoefList-class methods**unlist(x)::**

It transforms a AutomorphismByCoefList-class object into an AutomorphismByCoef-class object.

as(x, "AutomorphismByCoefList"):

It transforms a 'list' of AutomorphismByCoef-class object into an AutomorphismByCoefList-class object.

See Also

[automorphism_bycoef](#)

[AutomorphismByCoefList-class](#) and [Automorphism-class](#)

Examples

```
## Let's transform a AutomorphismByCoefList-class object into an
## AutomorphismByCoef-class object
data("autby_coef")
unlist(autby_coef[1:2])

## Herein a 'list' object of AutomorphismByCoef-class objects
lista <- list(human = autby_coef[[1]], gorilla = autby_coef[[2]])

## Let's transform the the last list 'lista' into an
## AutomorphismByCoefList-class object
aut <- as(lista, "AutomorphismByCoefList")
aut

## Let's get the element names from object 'aut'
names(aut)

## Let's assign new names
names(aut) <- c("human_1", "gorilla_1")
names(aut)
```

AutomorphismByCoefList-class

A class definition for a list of AutomorphismByCoef class objects.

Description

A class definition for a list of AutomorphismByCoef class objects.

Details

AutomorphismByCoefList-class has the following methods:

as('from', "AutomorphismByCoefList"):

Where 'from' is a list of **AutomorphismByCoef-class**.

unlist(x):

Where 'x' is a an **AutomorphismByCoefList-class** object.

Value

AutomorphismByCoefList-class definition.

See Also

[AutomorphismByCoef-class](#) and [AutomorphismList-class](#)

automorphismByRanges *Get the automorphisms by ranges.*

Description

Automorphisms estimated on a pairwise or a MSA alignment can be grouped by ranges which inherits from [GRanges-class](#) or a [GRanges-class](#).

Usage

```
automorphismByRanges(x, ...)

## S4 method for signature 'Automorphism'
automorphismByRanges(x)

## S4 method for signature 'AutomorphismList'
automorphismByRanges(
  x,
  min.len = 0L,
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

x	An AutomorphismList-class object returned by function automorphisms .
...	Not in use.
min.len	Minimum length of a range to be reported.
num.cores, tasks	Integers. Argument <i>num.cores</i> denotes the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply function from BiocParallel package). Argument <i>tasks</i> denotes the number of tasks per job. value must be a scalar integer $\geq 0L$. In this documentation a job is defined as a single call to a function, such as bplapply . A task is the division of the <i>X</i> argument into chunks. When <i>tasks</i> == 0 (default), <i>X</i> is divided as evenly as possible over the number of workers (see MulticoreParam from BiocParallel package).
verbose	logic(1). If TRUE, enable progress bar.

Value

A [GRanges-class](#) or a [GRangesList-class](#). Each [GRanges-class](#) object with a column named *cube*, which carries the type of *cube* automorphisms.

Examples

```
## Load dataset
data("autm", package = "GenomAutomorphism")

automorphismByRanges(x = autm[c(1, 4)])
```

AutomorphismList-class*A class definition to store list of Automorphism class objects.*

Description

A class definition to store list of Automorphism class objects derived from the pairwise automorphism estimation from pairwise alignments. Objects from this class are created by function [automorphisms](#) and [as.AutomorphismList](#).

Usage

```
## S4 method for signature 'AutomorphismList'
names(x)

## S4 replacement method for signature 'AutomorphismList,ANY'
names(x) <- value

## S4 method for signature 'AutomorphismList'
as.list(x)

## S4 method for signature 'AutomorphismList'
show(object)
```

Arguments

x	An AutomorphismList-class object.
value	A character vector naming the elements of the AutomorphismList-class object 'x'.
object	An object from AutomorphismList-class .

Value

An object from AutomorphismList-class

AutomorphismList-class methods

as.AutomorphismList(x):

as.AutomorphismList function transform a list of [GRanges-class](#), a [GRangesList-class](#), a list of [data.frame](#) or a [DataFrame-class](#) objects into a **AutomorphismList-class** object.

unlist(x):

It transforms a AutomorphismList-class object into an Automorphism-class object.

as.list(x):

It transforms a list of Automorphism-class objects into an AutomorphismList-class object.

as(x, "GRangesList"):

It transforms a [GRangesList](#) of [Automorphism-class](#) objects into an 'AutomorphismList-class' object.

names(x):

To get the element's names from an 'AutomorphismList-class' object.

names(x) <- value:

To assign names to the element from an 'AutomorphismList-class' object.

See Also

[Automorphism-class](#) and [AutomorphismByCoefList-class](#).

Examples

```
## Load datasets
data("autm", "brca1_autm")

## Transforming a list of Automorphisms into an AutomorphismList object
lista <- list(human = brca1_autm[[1]], gorilla = brca1_autm[[2]])
as.AutomorphismList(lista)

## Alternatively we can set
aut <- as.list(brca1_autm[seq(2)])
class(aut)

## And reverse it
aut <- as.AutomorphismList(aut)
aut

## Let's get the element names from object 'aut'
names(aut)

## Let's assign new names
names(aut) <- c("human_1", "gorilla_1")
names(aut)

## Transforming a GRangesList of Automorphisms into an AutomorphismList
## object
lista <- as(lista, "GRangesList")
as.AutomorphismList(lista)

## Transform a AutomorphismList-class object into an Automorphism-class
## object
unlist(brca1_autm[seq(2)])
## Load a DNA sequence alignment
data("brca1_autm", package = "GenomAutomorphism")
names(brca1_autm)
## Load a DNA sequence alignment
data("brca1_autm", package = "GenomAutomorphism")
x1 <- brca1_autm[seq(2)]
names(x1)
```

```
## Let's assign a new names
names(x1) <- c("human_1.human_2.0", "human_1.gorilla_0")
names(x1)
## Load a DNA sequence alignment
data("brca1_autm", package = "GenomAutomorphism")

## The list of the first three elements
autm_list <- as.list(brca1_autm[seq(3)])
autm_list
```

automorphisms	<i>Compute the Automorphisms of Mutational Events Between two Codon Sequences Represented in a Given Abelian group.</i>
---------------	---

Description

Given two codon sequences represented in a given Abelian group, this function computes the automorphisms describing codon mutational events. Basically, this function is a wrapping to call the corresponding function for a specified Abelian group.

Usage

```
automorphisms(seqs = NULL, filepath = NULL, group = "Z4", ...)
```

```
## S4 method for signature 'DNASet_OR_NULL'
automorphisms(
  seqs = NULL,
  filepath = NULL,
  group = c("Z5", "Z64", "Z125", "Z5^3"),
  cube = c("ACGT", "TGCA"),
  cube_alt = c("CATG", "GTAC"),
  nms = NULL,
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

seqs	An object from a DNASet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences. The pairwise alignment provided in argument seq or the 'fasta' file filepath must correspond to codon sequences.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
group	A character string denoting the group representation for the given base or codon as shown in reference (1).

...	Not in use.
cube, cube_alt	A character string denoting pairs of the 24 Genetic-code cubes, as given in references (2-3). That is, the base pairs from the given cubes must be complementary each other. Such a cube pair are call <i>dualcubes</i> and, as shown in reference (3), each pair integrates group.
nms	Optional. Only used if the DNA sequence alignment provided carries more than two sequences. A character string giving short names for the alignments to be compared. If not given then the automorphisms between pairwise alignment are named as: 'aln_1', 'aln_2', and so on.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Herein, automorphisms are algebraic descriptions of mutational event observed in codon sequences represented on different Abelian groups. In particular, as described in references (3-4), for each representation of the codon set on a defined Abelian group there are 24 possible isomorphic Abelian groups. These Abelian groups can be labeled based on the DNA base-order used to generate them. The set of 24 Abelian groups can be described as a group isomorphic to the symmetric group of degree four (S_4 , see reference (4)). Function [automorphismByRanges](#) permits the classification of the pairwise alignment of protein-coding sub-regions based on the mutational events observed on it and on the genetic-code cubes that describe them.

Automorphisms in Z_5 , Z_{64} and Z_{125} are described as functions $f(x) = kx \bmod 64$ and $f(x) = kx \bmod 125$, where k and x are elements from the set of integers modulo 64 or modulo 125, respectively. If an automorphisms cannot be found on any of the cubes provided in the argument *cube*, then function [automorphisms](#) will search for automorphisms in the cubes provided in the argument *cube_alt*.

Automorphisms in Z_5^3 are described as functions $f(x) = Ax \bmod Z_5$, where A is diagonal matrix.

Arguments **cube** and **cube_alt** must be pairs of dual cubes (see section 2.4 from reference 4).

Value

This function returns a [Automorphism-class](#) object with four columns on its metacolumn named: *seq1*, *seq2*, *autm*, and *cube*.

Methods

[automorphismByRanges::](#)

This function returns a [GRanges-class](#) object. Consecutive mutational events (on the codon sequence) described by automorphisms on a same cube are grouped in a range.

[automorphism_bycoef:](#)

This function returns a [GRanges-class](#) object. Consecutive mutational events (on the codon sequence) described by the same automorphisms coefficients are grouped in a range.

getAutomorphisms:

This function returns an AutomorphismList-class object as a list of Automorphism-class objects, which inherits from GRanges-class objects.

conserved_regions:

Returns a AutomorphismByCoef class object containing the requested regions.

Author(s)

Robersy Sanchez (<https://genomaths.com>).

References

1. Sanchez R, Morgado E, Grau R. Gene algebra from a genetic code algebraic structure. J Math Biol. 2005 Oct;51(4):431-57. doi: 10.1007/s00285-005-0332-8. Epub 2005 Jul 13. PMID: 16012800. ([PDF](#)).
2. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi:[10.1101/2021.06.01.446543](https://doi.org/10.1101/2021.06.01.446543)
3. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 110-152.[PDF](#).
4. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#)

See Also

[autZ64](#).

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Automorphism on "Z5^3"
autms <- automorphisms(seqs = aln, group = "Z5^3", verbose = FALSE)
autms

## Automorphism on "Z64"
autms <- automorphisms(seqs = aln, group = "Z64", verbose = FALSE)
autms

## Automorphism on "Z64" from position 1 to 33
autms <- automorphisms(
  seqs = aln,
  group = "Z64",
  start = 1,
  end = 33,
  verbose = FALSE
)
autms
```

automorphism_bycoef *Automorphism Grouping by Coefficient*

Description

Automorphisms with the same automorphism's coefficients are grouped.

Usage

```
automorphism_bycoef(x, ...)

## S4 method for signature 'Automorphism'
automorphism_bycoef(x, mut.type = TRUE)

## S4 method for signature 'AutomorphismList'
automorphism_bycoef(
  x,
  min.len = 1L,
  mut.type = TRUE,
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

<code>x</code>	An automorphism-class object returned by function automorphisms .
<code>...</code>	Not in use.
<code>mut.type</code>	Logical. Whether to include the mutation type as given by function mut_type .
<code>min.len</code>	Minimum length of a range to be reported.
<code>num.cores, tasks</code>	Integers. Argument <i>num.cores</i> denotes the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply function from BiocParallel package). Argument <i>tasks</i> denotes the number of tasks per job. value must be a scalar integer $\geq 0L$. In this documentation a job is defined as a single call to a function, such as bplapply . A task is the division of the <i>X</i> argument into chunks. When <code>tasks == 0</code> (default), <i>X</i> is divided as evenly as possible over the number of workers (see MulticoreParam from BiocParallel package).
<code>verbose</code>	logic(1). If TRUE, enable progress bar.

Value

An [AutomorphismByCoef](#) class object. A coefficient with 0 value is assigned to mutational events that are not automorphisms, e.g., indel mutations.

See Also

[automorphisms](#)

Examples

```
## Load dataset
data("autm", package = "GenomAutomorphism")

automorphism_bycoef(x = autm[1:2])
```

autZ125	<i>Compute the Automorphisms of Mutational Events Between two Codon Sequences Represented in Z125.</i>
---------	--

Description

Given two codon sequences represented in the Z125 Abelian group, this function computes the automorphisms describing codon mutational events.

Usage

```
autZ125(
  seq = NULL,
  filepath = NULL,
  cube = c("ACGT", "TGCA"),
  cube_alt = c("CATG", "GTAC"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  genetic_code = getGeneticCode("1"),
  num.cores = multicoreWorkers() - 1,
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

seq	An object from a DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences. The pairwise alignment provided in argument seq or the 'fasta' file filepath must correspond to codon sequences.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
cube, cube_alt	A character string denoting pairs of the 24 Genetic-code cubes, as given in references (2-3). That is, the base pairs from the given cubes must be complementary each other. Such a cube pair are call dual cubes and, as shown in reference (3), each pair integrates group.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
genetic_code	The named character vector returned by getGeneticCode or similar. The translation of codon into aminoacids is a valuable information useful for downstream statistical analysis. The standard genetic code is the default argument value applied in the translation of codons into aminoacids (see GENETIC_CODE_TABLE).

num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Automorphisms in Z125 are described as functions $f(x) = kx \bmod 64$, where k and x are elements from the set of integers modulo 64. As noticed in reference (1)

Value

An object [Automorphism-class](#) with four columns on its metacolumn named: *seq1*, *seq2*, *autm*, and *cube*.

References

1. Sanchez R, Morgado E, Grau R. Gene algebra from a genetic code algebraic structure. J Math Biol. 2005 Oct;51(4):431-57. doi: 10.1007/s00285-005-0332-8. Epub 2005 Jul 13. PMID: 16012800. ([PDF](#)).
2. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi:10.1101/2021.06.01.446543
3. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 110-152.[PDF](#).
4. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#)

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Automorphism on Z125
autms <- autZ125(seq = aln)
autms
```

autZ5	<i>Compute the Automorphisms of Mutational Events Between two Codon Sequences Represented in Z5.</i>
-------	--

Description

Given two codon sequences represented in the Z5 Abelian group, this function computes the automorphisms describing codon mutational events.

Usage

```
autZ5(
  seq = NULL,
  filepath = NULL,
  cube = c("ACGT", "TGCA"),
  cube_alt = c("CATG", "GTAC"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

seq	An object from a DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
cube, cube_alt	A character string denoting pairs of the 24 Genetic-code cubes, as given in references (2-3). That is, the base pairs from the given cubes must be complementary each other. Such a cube pair are call dual cubes and, as shown in reference (3), each pair integrates group.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Automorphisms in Z5 are described as functions $f(x) = kx \bmod 64$, where k and x are elements from the set of integers modulo 64. As noticed in reference (1). The pairwise alignment provided in argument **seq** or the 'fasta' file **filepath** must correspond to DNA base sequences.

Value

An object [Automorphism-class](#) with four columns on its metacolumn named: *seq1*, *seq2*, *autm*, and *cube*.

References

1. Sanchez R, Morgado E, Grau R. Gene algebra from a genetic code algebraic structure. J Math Biol. 2005 Oct;51(4):431-57. doi: 10.1007/s00285-005-0332-8. Epub 2005 Jul 13. PMID: 16012800. ([PDF](#)).

2. Roberisy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi:10.1101/2021.06.01.446543
3. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 110-152. [PDF](#).
4. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#)

See Also

[automorphisms](#)

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Automorphism on Z5
autms <- autZ5(seq = aln, verbose = FALSE)
autms
```

autZ64

Compute the Automorphisms of Mutational Events Between two Codon Sequences Represented in Z64.

Description

Given two codon sequences represented in the Z64 Abelian group, this function computes the automorphisms describing codon mutational events.

Usage

```
autZ64(
  seq = NULL,
  filepath = NULL,
  cube = c("ACGT", "TGCA"),
  cube_alt = c("CATG", "GTAC"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  genetic_code = getGeneticCode("1"),
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

seq	An object from a DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences. The pairwise alignment provided in argument seq or the 'fasta' file filepath must correspond to codon sequences.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
cube, cube_alt	A character string denoting pairs of the 24 Genetic-code cubes, as given in references (2-3). That is, the base pairs from the given cubes must be complementary each other. Such a cube pair are call dual cubes and, as shown in reference (3), each pair integrates group.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
genetic_code	The named character vector returned by getGeneticCode or similar. The translation of codon into aminoacids is a valuable information useful for downstream statistical analysis. The standard genetic code is the default argument value applied in the translation of codons into aminoacids (see GENETIC_CODE_TABLE).
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the progress bar.

Details

Automorphisms in Z64 are described as functions $f(x) = k * x \bmod 64$, where k and x are elements from the set of integers modulo 64.

Value

An object [Automorphism-class](#) with four columns on its metacolumn named: *seq1*, *seq2*, *autm*, and *cube*.

Author(s)

Robersy Sanchez (<https://genomaths.com>).

References

1. Sanchez R, Morgado E, Grau R. Gene algebra from a genetic code algebraic structure. J Math Biol. 2005 Oct;51(4):431-57. doi: 10.1007/s00285-005-0332-8. Epub 2005 Jul 13. PMID: 16012800. ([PDF](#)).
2. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi:10.1101/2021.06.01.446543
3. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 110-152.[PDF](#).
4. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#)

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Automorphism on Z64
autms <- autZ64(seq = aln, verbose = FALSE)
autms
```

base2codon

*Split a DNA sequence into codons***Description**

This function split a DNA sequence into a codon sequence.

Usage

```
base2codon(x, ...)

## S4 method for signature 'character'
base2codon(x)

## S4 method for signature 'DNAStrngSet'
base2codon(x)

## S4 method for signature 'DNAMultipleAlignment'
base2codon(x)
```

Arguments

x	A character string, DNAStrngSet-class or DNAMultipleAlignment-class object carrying the a DNA sequence.
...	Not in use.

Details

It is expected that the provided DNA sequence is multiple of 3, otherwise gaps are added to the end of the sequence.

Value

If the argument of 'x' is character string, then a character vector of codons will returned. If the argument of 'x' is [DNAStrngSet-class](#) or [DNAMultipleAlignment-class](#) object, then a matrix of codons is returned.

Author(s)

Robersy Sanchez <https://genomaths.com>. 01/15/2022

Examples

```
## Gaps are added at the sequence end.
seq <- c("ACCT")
base2codon(x = seq)

## This DNA sequence is multiple of 3
seq <- c("ACCTCA")
base2codon(x = seq)

## Load a DNASTringSet. A matrix of codons is returned
data("aln", package = "GenomAutomorphism")
base2codon(x = aln)
```

base2int

*Replace bases with integers from Z4 and Z5***Description**

A simple function to represent DNA bases as elements from the Abelian group of integers modulo 4 (Z4), 5 (Z5), or 2 (Z2).

Usage

```
base2int(base, ...)
```

```
## S4 method for signature 'character'
base2int(
  base,
  group = c("Z4", "Z5", "Z64", "Z125", "Z4^3", "Z5^3", "Z2"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  phychem = list(A = NULL, T = NULL, C = NULL, G = NULL, N = NULL)
)
```

```
## S4 method for signature 'data.frame'
base2int(
  base,
  group = c("Z4", "Z5", "Z64", "Z125", "Z4^3", "Z5^3", "Z2"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  phychem = list(A = NULL, T = NULL, C = NULL, G = NULL, N = NULL)
)
```

Arguments

base	A character vector, string , or a dataframe of letters from the DNA/RNA alphabet.
...	Not in use.

group	A character string denoting the group representation for the given base or codon as shown in reference (2-3).
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).
phychem	Optional. Eventually, it could be useful to represent DNA bases by numerical values of measured physicochemical properties. If provided, then this argument must be a named numerical list. For example, the scale values of deoxyribonucleic acids proton affinity (available at https://www.wolframalpha.com/ and in cell phone app: Wolfram Alpha): $list('A' = 0.87, 'C' = 0.88, 'T' = 0.82, 'G' = 0.89, 'N' = NA)$ where symbol 'N' provide the value for any letter out of DNA base alphabet. In this example, we could write NA or 0 (see example section).

Details

For Z2 (binary representation of DNA bases), the cube bases are represented in their order by: '00', '01', '10', and '11' (examples section).

Value

A numerical vector.

Author(s)

Robersy Sanchez <https://genomaths.com>

References

1. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi: [10.1101/2021.06.01.446543](https://doi.org/10.1101/2021.06.01.446543)
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152. [PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560.

See Also

[base_coord](#), [codon_coord](#), and [dna_phychem](#).

Examples

```
## A triplet with a letter not from DNA/RNA alphabet
## 'NA' is introduced by coercion!
base2int("UDG")

## The base replacement in cube "ACGT and group "Z4"
base2int("ACGT")

## The base replacement in cube "ACGT and group "Z5"
base2int("ACGT", group = "Z5")

## A vector of DNA base triplets
```



```

base2int(c("UTG", "GTA"))

## A vector of DNA base triplets with different number of triplets.
## Codon 'GTA' is recycled!
base2int(base = c("UTGGTA", "CGA"), group = "Z5")

## Data frames

base2int(data.frame(x1 = c("UTG", "GTA"), x2 = c("UTG", "GTA")))

## Cube bases are represented in their order by: '00', '01', '10', and '11',
## For example for cube = "ACGT" we have mapping: A -> '00', C -> '01',
## G -> '11', and T -> '10'.

base2int("ACGT", group = "Z2", cube = "ACGT")

```

BaseGroup-class	<i>A class definition to store codon automorphisms in given in the Abelian group representation.</i>
-----------------	--

Description

A class definition to store codon automorphisms in given in the Abelian group representation.

Value

Given the slot values define a BaseGroup-class.

See Also

[automorphisms](#)

BaseGroup_OR_CodonGroup-class	<i>A definition for the union of classes 'BaseGroup' and 'CodonGroup'</i>
-------------------------------	---

Description

A definition for the union of classes 'BaseGroup' and 'CodonGroup'

See Also

[BaseGroup](#) and [CodonGroup](#).

BaseSeq-class	<i>A class definition to store DNA base sequence.</i>
---------------	---

Description

A class definition to store DNA base sequence.

Value

Given the slot values define a BaseSeq-class.

See Also

[automorphisms](#)

BaseSeqMatrix-class	<i>A class definition to Store DNA base sequence coordinates in a given Genetic Code Cube.</i>
---------------------	--

Description

A class definition to Store DNA base sequence coordinates in a given Genetic Code Cube.

Value

Given the slot values define a BaseSeq-class.

See Also

[automorphisms](#)

base_coord	<i>DNA Sequences Methods</i>
------------	------------------------------

Description

Base coordinates on a given Abelian group representation:

Given a string denoting a codon or base from the DNA (or RNA) alphabet, function *base_coord* return the base coordinates in the specify genetic-code Abelian group, as given in reference (1).

DNA sequences to GRanges of bases.:

Function *seq2granges* transform an object from [DNASTringSet](#), [DNAMultipleAlignment-class](#) or a character into an object from [BaseSeq](#).

BaseSeq-class object to DNASTringSet-class object.:

Function *base_seq2string_set* transforms an object from [BaseSeq](#) into an object from [DNASTringSet-class](#).

Usage

```

base_coord(base = NULL, filepath = NULL, cube = "ACGT", group = "Z4", ...)

## S4 method for signature 'DNASTringSet_OR_NULL'
base_coord(
  base = NULL,
  filepath = NULL,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z4", "Z5"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+"
)

seq2granges(base = NULL, filepath = NULL, ...)

## S4 method for signature 'DNASTringSet_OR_NULL'
seq2granges(
  base = NULL,
  filepath = NULL,
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+",
  seq_alias = NULL,
  ...
)

base_seq2string_set(x, ...)

## S4 method for signature 'BaseSeq'
base_seq2string_set(x)

base_matrix(base, ...)

## S4 method for signature 'DNASTringSet_OR_NULL'
base_matrix(
  base,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z4", "Z5"),
  seq_alias = NULL
)

```

Arguments

base An object from a [DNASTringSet](#) or [DNAMultipleAlignment](#) class carrying the DNA pairwise alignment of two sequences.

filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2 2 3).
group	A character string denoting the group representation for the given base or codon as shown in reference (1).
...	Not in use yet.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.
seq_alias	DNA sequence alias/ID and description.
x	A 'BaseSeq' class object.

Details

Function 'base_coord':

Function *base_coord* is defined only for pairwise aligned sequences. Symbols "-" and "N" usually found in DNA sequence alignments to denote gaps and missing/unknown bases are represented by the number: '-1' on Z4 and '0' on Z5. In Z64 the symbol 'NA' will be returned for codons including symbols "-" and "N".

Functions 'seq2granges' and 'base_seq2string_set':

For the sake of brevity the metacolumns from the object returned by function 'seq2granges' are named as 'S1', 'S2', 'S3', and so on. The original DNA sequence alias are stored in the slot named 'seq_alias'. (see examples).

Value

Depending on the function called, different object will be returned:

Function 'base_coord':

This function returns a [BaseGroup](#) object carrying the DNA sequence(s) and their respective coordinates in the requested Abelian group of base representation (one-dimension, "Z4" or "Z5"). Observe that to get coordinates in the set of of integer numbers ("Z") is also possible but they are not defined to integrate a Abelian group. These are just used for the further insertion the codon set in the 3D space (R^3).

Function 'seq2granges':

This function returns a [BaseGroup](#) object carrying the DNA sequence(s), one base per ranges. A [BaseGroup](#) class object inherits from [GRanges-class](#).

Function 'base_seq2string_set':

This function returns a [DNAStringSet-class](#).

A [BaseGroup-class](#) object.

Author(s)

Robersy Sanchez <https://genomaths.com>

References

1. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi:10.1101/2021.06.01.446543
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152.PDF.
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560.

See Also

[Symmetric Group of the Genetic-Code Cubes.](#)

[codon_coord](#) and [base2int](#).

[Symmetric Group of the Genetic-Code Cubes.](#)

[base_coord](#) and [codon_coord](#).

Examples

```
## Example 1. Let's get the base coordinates for codons "ACG"
## and "TGC":
x0 <- c("ACG", "TGC")
x1 <- DNAStrngSet(x0)
x1

## Get the base coordinates on cube = "ACGT" on the Abelian group = "Z4"
base_coord(x1, cube = "ACGT", group = "Z4")

## Example 2. Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## DNA base representation in the Abelian group Z4
bs_cor <- base_coord(
  base = aln,
  cube = "ACGT"
)
bs_cor

## Example 3. DNA base representation in the Abelian group Z5
bs_cor <- base_coord(
  base = aln,
  cube = "ACGT",
  group = "Z5"
)
bs_cor

## Example 4. Load a multiple sequence alignment (MSA) of primate BRCA1 DNA
## repair genes
data("brca1_aln2", package = "GenomAutomorphism")
brca1_aln2

## Get BaseSeq-class object
gr <- seq2granges(brca1_aln2)
gr
```

```
## Transform the BaseSeq-class object into a DNASTringSet-class object
str_set <- base_seq2string_set(gr)
str_set

## Recovering the original MSA
DNAMultipleAlignment(as.character(str_set))

## Example 5.
base_matrix(base = aln, cube = "CGTA", group = "Z5")

## Example 5.
```

base_repl	<i>Replace bases with integers</i>
-----------	------------------------------------

Description

Replace bases with integers

Usage

```
base_repl(base, cube, group, phychem)
```

Details

Internal use only.

Value

A numerical vector.

brca1_aln	<i>Multiple Sequence Alignment (MSA) of Primate BRCA1 DNA repair genes.</i>
-----------	---

Description

This is a `DNAMultipleAlignment` carrying a MSA of **BRCA1 DNA repair genes** to be used in the examples provided for the package functions. The original file can be downloaded from GitHub at: <https://bit.ly/3DimROD>

Usage

```
data("brca1_aln", package = "GenomAutomorphism")
```

Format

`DNAMultipleAlignment` class object.

See Also

[brca1_aln2](#), [brca1_autm](#), and [covid_aln](#).

Examples

```
data("brca1_aln", package = "GenomAutomorphism")
brca1_aln
```

brca1_aln2

Multiple Sequence Alignment (MSA) of Primate BRCA1 DNA repair genes.

Description

This is a [DNAMultipleAlignment](#) carrying a MSA of **BRCA1 DNA repair genes** to be used in the examples provided for the package functions. The original file can be downloaded from GitHub at: <https://bit.ly/3DimROD>. This data set has 41 DNA sequences and it contains the previous 20 primate variants found in 'brca1_aln' data set plus 21 single mutation variants (SMV) from the human sequence NM_007298 transcript variant 4. The location of each SMV is given in the heading from each sequence.

Usage

```
data("brca1_aln2", package = "GenomAutomorphism")
```

Format

[DNAMultipleAlignment](#) class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_aln](#), [brca1_autm2](#), [cyc_aln](#), and [covid_autm](#).

Examples

```
data("brca1_aln2", package = "GenomAutomorphism")
brca1_aln2
```

brca1_autm

*Automorphisms between DNA Sequences from Primate BRCA1 Genes***Description**

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the DNA sequences from the MSA of primate BRCA1 DNA repair gene. The automorphisms were estimated from the [brca1_aln](#) MSA with function [autZ64](#).

Usage

```
data("brca1_autm", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_autm2](#), [brca1_aln](#), [brca1_aln2](#), and [covid_autm](#).

Examples

```
data("brca1_autm", package = "GenomAutomorphism")
brca1_autm
```

brca1_autm2

*Automorphisms between DNA Sequences from Primate BRCA1 Genes***Description**

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the DNA sequences from the MSA of primate BRCA1 DNA repair gene. The data set [brca1_aln2](#) has 41 DNA sequences and it contains the previous 20 primate variants found in 'brca1_aln' data set plus 21 single mutation variants (SMV) from the human sequence NM_007298 transcript variant 4. The location of each SMV is given in the heading from each sequence. The automorphisms were estimated from the [brca1_aln](#) MSA with function [autZ64](#).

Usage

```
data("brca1_autm2", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

cdm_z64

*Codon Distance Matrices for the Standard Genetic Code on Z4***Description**

This is a list of 24 codon distance matrices created with function [codon_dist_matrix](#) in the set of 24 genetic-code cubes on Z4 (using the default weights and assuming the standard genetic code (SGC)). The data set is created to speed up the computation when working with DNA sequences from superior organisms. Since distance matrices are symmetric, it is enough to provide the lower matrix. Each matrix is given as named/labeled vector (see the example).

Usage

```
data("cdm_z64", package = "GenomAutomorphism")
```

Format

A list object.

Examples

```
## Load the data set
data("cdm_z64", package = "GenomAutomorphism")
cdm_z64

## The lower matrix (given as vector) for cube "TCGA" (picking out the 20
## first values). Observe that this vector is labeled. Each numerical value
## corresponds to the distance between the codons specified by the
## name/label on it. For example, the distance between codons TTT and TCT
## is: 0.0625.

head(cdm_z64[[ "TCGA" ]], 20)
```

CodonGroup-class

A class definition to store codon automorphisms in given in the Abelian group representation.

Description

A class definition to store codon automorphisms in given in the Abelian group representation.

Value

Given the slot values define a CodonGroup-class.

See Also

[automorphisms](#)

CodonMatrix-class	<i>A Convenient Class to Store a Codon Coordinate in given Genetic Code cube.</i>
-------------------	---

Description

A CodonMatrix is the object created by function [codon_matrix](#)

Usage

```
CodonMatrix(object, group, cube, seq_alias = NULL)
```

Arguments

object	A GRanges-class object.
group	The name of the base group, 'Z4' or 'Z5'.
cube	The name of the genetic-code cube applied to get the codon coordinates.
seq_alias	The 'alias' given to the codon sequence.

Value

A 'CodonMatrix' class object

See Also

[base_coord](#) and [codon_coord](#).

Examples

```
## CodonMatrix is generated by function 'codon_matrix' (inside a
## ListCodonMatrix-class object)
## Let's create DNASTringSet-class object
base <- DNASTringSet(x = c(S1 = 'ACGTGATCAAGT'))

x1 <- codon_matrix(base)
x1

## Extract the first element
x1[1]
x1$codon.1
x1[[1]]
```

CodonSeq-class	<i>A class definition to store codon coordinates given in the Abelian group and the codon sequence.</i>
----------------	---

Description

An objects from 'CodonSeq' or 'MatrixList' class is returned by function [get_coord](#). This object will store the coordinate of each sequence in a list of 3D-vectors or a list of vectors located in the slot named 'CoordList'. The original codon sequence (if provided) will be stored in the slot named 'SeqRanges'.

Usage

```
coordList(x)

## S4 method for signature 'CodonSeq'
coordList(x)

seqRanges(x)

## S4 method for signature 'CodonSeq'
seqRanges(x)
```

Arguments

x An object from [CodonSeq-class](#).

Value

Given the slot values define a CodonSeq-class.

Examples

```
## Load a DNA sequence alignment
data("aln", package = "GenomAutomorphism")

## Get base coordinates on 'Z5'
coord <- get_coord(
  x = aln,
  cube = "ACGT",
  group = "Z5"
)
coordList(coord)
## Load a DNA sequence alignment
data("aln", package = "GenomAutomorphism")

## Get base coordinates on 'Z5'
coord <- get_coord(
  x = aln,
  cube = "ACGT",
  group = "Z5"
)

seqRanges(coord)
```

codon_coord

*Codon coordinates on a given a given Abelian group representation.***Description**

Given a string denoting a codon or base from the DNA (or RNA) alphabet and a genetic-code Abelian group as given in reference (1).

Usage

```
codon_coord(codon = NULL, ...)

## S4 method for signature 'BaseGroup'
codon_coord(codon, group = NULL)

## S4 method for signature 'DNASet_OR_NULL'
codon_coord(
  codon = NULL,
  filepath = NULL,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z4", "Z5", "Z64", "Z125", "Z4^3", "Z5^3"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+"
)

## S4 method for signature 'matrix_OR_data_frame'
codon_coord(
  codon,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z64", "Z125", "Z4^3", "Z5^3")
)
```

Arguments

codon	An object from BaseGroup-class (generated with function base_coord), DNASet or from DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences.
...	Not in use.
group	A character string denoting the group representation for the given base or codon as shown in reference (2-3).
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).

start, end, chr, strand

Optional parameters required to build a [GRanges-class](#). If not provided the default values given for the function definition will be used.

Details

Symbols "-" and "N" usually found in DNA sequence alignments to denote gaps and missing/unknown bases are represented by the number: '-1' on Z4 and '0' on Z5. In Z64 the symbol 'NA' will be returned for codons including symbols "-" and "N".

This function returns a [GRanges-class](#) object carrying the codon sequence(s) and their respective coordinates in the requested Abelian group or simply, when *group* = 'Z5^3' 3D-coordinates, which are derived from Z5 as indicated in reference (3). Notice that the coordinates can be 3D or just one-dimension ("Z64" or "Z125"). Hence, the pairwise alignment provided in argument **codon** must correspond to codon sequences.

Value

A [CodonGroup-class](#) object.

Author(s)

Robersy Sanchez <https://genomaths.com>

References

1. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi: [10.1101/2021.06.01.446543](https://doi.org/10.1101/2021.06.01.446543)
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152. [PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560.

See Also

[Symmetric Group of the Genetic-Code Cubes](#).
[codon_matrix](#), [base_coord](#) and [base2int](#).

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## DNA base representation in the Abelian group Z5
bs_cor <- codon_coord(
  codon = aln,
  cube = "ACGT",
  group = "Z5"
)
bs_cor ## 3-D coordinates

## DNA base representation in the Abelian group Z64
```

```
bs_cor <- codon_coord(
  codon = aln,
  cube = "ACGT",
  group = "Z64"
)
bs_cor

## Giving a matrix of codons
codon_coord(base2codon(x = aln))
```

codon_dist

Weighted Manhattan Distance Between Codons

Description

This function computes the weighted Manhattan distance between codons from two sequences as given in reference (1). That is, given two codons x and y with coordinates on the set of integers modulo 5 ("Z5"): $x = (x_1, x_2, x_3)$ and $y = (y_1, y_2, y_3)$ (see (1)), the Weighted Manhattan distance between this two codons is defined as:

$$d_w(x, y) = |x_1 - y_1|/5 + |x_2 - y_2| + |x_3 - y_3|/25$$

If the codon coordinates are given on "Z4", then the Weighted Manhattan distance is define as:

$$d_w(x, y) = |x_1 - y_1|/4 + |x_2 - y_2| + |x_3 - y_3|/16$$

Herein, we move to the generalized version given in reference (3), for which:

$$d_w(x, y) = |x_1 - y_1|w_1 + |x_2 - y_2|w_2 + |x_3 - y_3|w_3$$

where we use the vector of *weight* = (w_1, w_2, w_3) .

Usage

```
codon_dist(x, y, ...)
```

```
## S4 method for signature 'DNAStringSet'
codon_dist(
  x,
  weight = NULL,
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)
```

```
## S4 method for signature 'character'
```

```

codon_dist(
  x,
  y,
  weight = NULL,
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
            "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
            "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)

## S4 method for signature 'CodonGroup_OR_Automorphisms'
codon_dist(
  x,
  weight = NULL,
  group = c("Z4", "Z5"),
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
            "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
            "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE
)

```

Arguments

<code>x, y</code>	A character string of codon sequences, i.e., sequences of DNA base-triplets. If only 'x' argument is given, then it must be a DNAStringSet-class object.
<code>...</code>	Not in use yet.
<code>weight</code>	A numerical vector of weights to compute weighted Manhattan distance between codons. If <i>weight</i> = <i>NULL</i> , then <i>weight</i> = (1/4, 1, 1/16) for <i>group</i> = "Z4" and <i>weight</i> = (1/5, 1, 1/25) for <i>group</i> = "Z5".
<code>group</code>	A character string denoting the group representation for the given codon sequence as shown in reference (2-3).
<code>cube</code>	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).
<code>num.cores, tasks</code>	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
<code>verbose</code>	If TRUE, prints the progress bar.

Value

A numerical vector with the pairwise distances between codons in sequences 'x' and 'y'.

References

1. Sanchez R. Evolutionary Analysis of DNA-Protein-Coding Regions Based on a Genetic Code Cube Metric. Curr Top Med Chem. 2014;14: 407–417. <https://doi.org/10.2174/15680266136661312041100>.
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152. [PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560. [PDF](#).

See Also

[codon_dist_matrix](#), [automorphisms](#), [codon_coord](#), and [aminoacid_dist](#).

Examples

```
## Let's write two small DNA sequences
x = "ACGCGTGACCGTGACTG"
y = "TGCGCCCGTGACGCGTGA"

codon_dist(x, y, group = "Z5")

## Alternatively, data can be vectors of codons, i.e., vectors of DNA
## base-triplets (including gaps simbol "-").
x = c("ACG", "CGT", "GTA", "CCG", "TGA", "CTG", "ACG")
y = c("TGC", "GCC", "CGT", "GAC", "---", "TGA", "A-G")

## Gaps are not defined on "Z4"
codon_dist(x, y, group = "Z4")

## Gaps are considered on "Z5"
codon_dist(x, y, group = "Z5")

## Load an Automorphism-class object
data("autm", package = "GenomAutomorphism")
codon_dist(x = head(autm, 20), group = "Z4")

## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

codon_dist(x = aln, group = "Z5")
```

codon_dist_matrix

Compute Codon Distance Matrix

Description

This function computes the codon distance matrix based on the weighted Manhattan distance between codons estimated with function [codon_dist](#).

Usage

```
codon_dist_matrix(
  genetic_code = "1",
  group = c("Z4", "Z5"),
  weight = NULL,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  output = c("list", "vector", "dist"),
  num.cores = 1L
)
```

Arguments

genetic_code	A single string that uniquely identifies the genetic code to extract. Should be one of the values in the id or name2 columns of GENETIC_CODE_TABLE .
group	A character string denoting the group representation for the given codon sequence as shown in reference (2-3).
weight	A numerical vector of weights to compute weighted Manhattan distance between codons. If <i>weight</i> = <i>NULL</i> , then <i>weight</i> = (1/4, 1, 1/16) for <i>group</i> = "Z4" and <i>weight</i> = (1/5, 1, 1/25) for <i>group</i> = "Z5" (see codon_dist).
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).
output	Format of the returned lower triangular matrix: as a list of 63 elements (labeled) or as a labeled vector using codons as labels.
num.cores	An integer to setup the number of parallel workers via makeCluster .

Details

By construction, a distance matrix is a symmetric matrix. Hence, the knowledge of lower triangular matrix is enough for its application to any downstream analysis.

Value

A lower triangular matrix excluding the diagonal.

See Also

[codon_dist](#).

Examples

```
## The distance matrix for codons for the Invertebrate Mitochondrial,
## cube "TGCA" with base-triplet represented on the group "Z5". Each
## coordinate from each returned numerical vector corresponds to the
## distance between codons given in the coordinate name.
x <- codon_dist_matrix(genetic_code = "5", cube = "TGCA", group = "Z5",
  output = "vector")
x[seq(61, 63)]
```

codon_matrix

*Codon Coordinate Matrix***Description**

This function build the coordinate matrix for each sequence from an aligned set of DNA codon sequences.

Usage

```
codon_matrix(base, ...)

## S4 method for signature 'BaseSeqMatrix'
codon_matrix(base, num.cores = 1L, tasks = 0L, verbose = TRUE, ...)

## S4 method for signature 'DNAStrngSet'
codon_matrix(
  base,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z4", "Z5"),
  num.cores = 1L,
  tasks = 0L,
  verbose = TRUE
)

## S4 method for signature 'DNAMultipleAlignment'
codon_matrix(
  base,
  cube = c("ACGT", "AGCT", "TCGA", "TGCA", "CATG", "GTAC", "CTAG", "GATC", "ACTG",
    "ATCG", "GTCA", "GCTA", "CAGT", "TAGC", "TGAC", "CGAT", "AGTC", "ATGC", "CGTA",
    "CTGA", "GACT", "GCAT", "TACG", "TCAG"),
  group = c("Z4", "Z5"),
  num.cores = 1L,
  tasks = 0L,
  verbose = TRUE
)
```

Arguments

base	A DNAMultipleAlignment , a DNAStrngSet , or a BaseSeqMatrix .
...	Not in use yet.
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the function log to stdout

cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (3-4).
group	A character string denoting the group representation for the given base or codon as shown in reference (3-4).

Details

The purpose of this function is making the codon coordinates from multiple sequence alignments (MSA) available for further downstream statistical analyses, like those reported in references (1) and (2).

Value

A [ListCodonMatrix](#) class object with the codon coordinate on its metacolumns.

Author(s)

Robersy Sanchez <https://genomaths.com>

References

1. Lorenzo-Ginori, Juan V., Aníbal Rodríguez-Fuentes, Ricardo Grau Ábalo, and Robersy Sánchez Rodríguez. "Digital signal processing in the analysis of genomic sequences." *Current Bioinformatics* 4, no. 1 (2009): 28-40.
2. Sanchez, Robersy. "Evolutionary analysis of DNA-protein-coding regions based on a genetic code cube metric." *Current Topics in Medicinal Chemistry* 14, no. 3 (2014): 407-417.
3. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi: [10.1101/2021.06.01.446543](https://doi.org/10.1101/2021.06.01.446543)
4. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, *Adv. Stud. Biol.* 4 (2012) 119-152.[PDF](#).
5. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process *MATCH Commun. Math. Comput. Chem.* 79 (2018) 527-560.
- 1.
- 2.

See Also

[codon_coord](#), [base_coord](#) and [base2int](#).

Examples

```
## Load the MSA of Primate BRCA1 DNA repair genes
data("brca1_aln")

## Get the DNAStringSet for the first 33 codons and apply 'codon_matrix'
brca1 <- unmasked(brca1_aln)
brca1 <- subseq(brca1, start = 1, end = 33)
codon_matrix(brca1)

## Get back the alignment object and apply 'codon_matrix' gives us the
## same result.
```

```
brca1 <- DNAMultipleAlignment(as.character(brca1))
codon_matrix(brca1)
```

ConservedRegion-class *A class definition to store conserved gene/genomic regions found in a MSA.*

Description

A class definition to store conserved gene/genomic regions found in a MSA.

Valid **ConservedRegion** mcols

A class definition for a list of **ConservedRegion** class objects.

Valid **ConservedRegionList** mcols

Usage

```
valid.ConservedRegion(x)
```

```
valid.ConservedRegionList(x)
```

Arguments

x A 'ConservedRegionList object'

Details

ConservedRegionList-class has the following method:

```
as('from', "ConservedRegionList"):
```

Where 'from' is a list of **ConservedRegion-class**.

Value

Definition of the **ConservedRegion-class**.

conserved_regions *Conserved and Non-conserved Regions from a MSA*

Description

Returns the Conserved or the Non-conserved Regions from a MSA.

Usage

```

conserved_regions(x, ...)

## S4 method for signature 'Automorphism'
conserved_regions(
  x,
  conserved = TRUE,
  output = c("all_pairs", "unique_pairs", "unique")
)

## S4 method for signature 'AutomorphismList'
conserved_regions(
  x,
  conserved = TRUE,
  output = c("all_pairs", "unique_pairs", "unique"),
  num.cores = multicoreWorkers(),
  tasks = 0L,
  verbose = FALSE
)

## S4 method for signature 'AutomorphismByCoef'
conserved_regions(
  x,
  conserved = TRUE,
  output = c("all_pairs", "unique_pairs", "unique")
)

## S4 method for signature 'AutomorphismByCoefList'
conserved_regions(
  x,
  conserved = TRUE,
  output = c("all_pairs", "unique_pairs", "unique")
)

```

Arguments

<code>x</code>	A Automorphism-class , a AutomorphismList-class , a AutomorphismByCoef or a AutomorphismByCoefList class object.
<code>...</code>	Not in use.
<code>conserved</code>	Logical, Whether to return the <i>conserved</i> or the <i>non-conserved regions</i> .
<code>output</code>	A character string. Type of output.
<code>num.cores, tasks</code>	Integers. Argument <i>num.cores</i> denotes the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply function from BiocParallel package). Argument <i>tasks</i> denotes the number of tasks per job. value must be a scalar integer $\geq 0L$. In this documentation a job is defined as a single call to a function, such as bplapply . A task is the division of the <i>X</i> argument into chunks. When <code>tasks == 0</code> (default), <i>X</i> is divided as evenly as possible over the number of workers (see MulticoreParam from BiocParallel package).
<code>verbose</code>	logic(1). If TRUE, enable progress bar.

Value

A `AutomorphismByCoef` class object containing the requested regions.

Examples

```
## Load dataset
data("autm", package = "GenomAutomorphism")
conserved_regions(autm[1:3])
## Load automorphism found COVID dataset
data("covid_autm", package = "GenomAutomorphism")

## Conserved regions in the first 100 codons
conserv <- conserved_regions(covid_autm[1:100], output = "unique")
conserv
```

covid_aln

Pairwise Sequence Alignment (MSA) of COVID-19 genomes.

Description

This is a `DNAMultipleAlignment` carrying the pairwise sequence alignment of SARS coronavirus GZ02 (GenBank: AY390556.1: 265-13398_13398-21485) and Bat SARS-like coronavirus isolate bat-SL-CoVZC45 (GenBank: MG772933.1:265-13455_13455-21542), complete genomes. The alignment is available at GitHub: <https://github.com/genomaths/seqalignments/tree/master/COVID-19>

Usage

```
data("covid_aln", package = "GenomAutomorphism")
```

Format

`DNAMultipleAlignment` class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_aln](#), [brca1_autm2](#), [cyc_aln](#) and [covid_aln](#).

Examples

```
data("covid_aln", package = "GenomAutomorphism")
covid_aln
```

covid_autm	<i>Automorphisms between DNA Sequences from two COVID-19 genomes</i>
------------	--

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the SARS coronavirus GZ02 (GenBank: AY390556.1: 265-13398_13398-21485) and Bat SARS-like coronavirus isolate bat-SL-CoVZC45 (GenBank: KY417151.1: protein-coding regions). The pairwise DNA sequence alignment is available in the dataset named [covid_aln](#) and the automorphisms were estimated with function [autZ64](#).

Usage

```
data("covid_autm", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_autm](#), [brca1_autm2](#), [cyc_autm](#), and [covid_aln](#).

Examples

```
data("covid_autm", package = "GenomAutomorphism",
      envir = environment())
covid_autm
```

cyc_aln	<i>Multiple Sequence Alignment (MSA) of Primate Somatic Cytochrome C</i>
---------	--

Description

This is a [DNAMultipleAlignment](#) carrying a MSA of **Primate Somatic Cytochrome C** to be used in the examples provided for the package functions. The original file can be downloaded from GitHub at: <https://bit.ly/3kdEAzs>

Usage

```
data("cyc_aln", package = "GenomAutomorphism")
```

Format

[DNAMultipleAlignment](#) class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_aln](#), [brca1_aln2](#), [covid_aln](#), and [covid_aln](#).

Examples

```
data("cyc_aln", package = "GenomAutomorphism")
cyc_aln
```

cyc_autm	<i>Automorphisms between DNA Sequences from Primate Cytochrome C Genes</i>
----------	--

Description

This is a [AutomorphismList](#) object carrying a list of pairwise automorphisms between the DNA sequences from the MSA of **Primate Somatic Cytochrome C** to be used in the examples provided for the package functions. The automorphisms were estimated from the [cyc_aln](#) MSA with function [autZ64](#).

Usage

```
data("cyc_autm", package = "GenomAutomorphism")
```

Format

[AutomorphismList](#) class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[brca1_autm](#), [brca1_autm2](#), [covid_autm](#), and [covid_aln](#).

Examples

```
data("cyc_autm", package = "GenomAutomorphism")
cyc_autm
```


Description

This data set carries some relevant physicochemical properties of the DNA bases. Available properties are:

"proton_affinity: " It is an indication of the thermodynamic gradient between a molecule and the anionic form of that molecule upon removal of a proton from it ([Wikipedia](#)). The proton affinity values, given in kJ/mol, were taken from reference (1), also available in Wolfram Alpha at <https://www.wolframalpha.com/> and in the cell phone App 'Wolfram Alpha'.. Reference (2) provides several measurements accomplished by several computational and experimental approaches.

"partition_coef: " 1-octanol/water partition coefficients, logP. In the physical sciences, a partition coefficient (P) or distribution coefficient (D) is the ratio of concentrations of a compound in a mixture of two immiscible solvents at equilibrium (3). The partition coefficient measures how hydrophilic ("water-loving") or hydrophobic ("water-fearing") a chemical substance is. Partition coefficients are useful in estimating the distribution of drugs within the body. Hydrophobic drugs with high octanol-water partition coefficients are mainly distributed to hydrophobic areas such as lipid bilayers of cells. Conversely, hydrophilic drugs (low octanol/water partition coefficients) are found primarily in aqueous regions such as blood serum. The partition coefficient values included here were taken from reference (1), also available in Wolfram Alpha at <https://www.wolframalpha.com/> and in the cell phone App 'Wolfram Alpha'.

"dipole_moment: " Dipole-dipole, dipole-induced-dipole and London force interactions among the bases in the helix are large, and make the free energy of the helix depend on the base composition and sequence. The dipole moment values were taken from reference (4). The dipole moment of DNA bases refers to the measure of polarity in the chemical bonds between atoms within the nucleobases. Dipole moments arise due to differences in electronegativity between the bonded atoms. In DNA bases, these dipole moments can influence the orientation of the bases when interacting with other molecules or surfaces, such as graphene/h-BN interfaces. The concept of dipole moments has been applied to analyze the electric moments of RNA-binding proteins, which can help identify DNA-binding proteins and provide insights into their mechanisms and prediction.

"tautomerization_energy: " The term "tautomerism" is usually defined as structural isomerism with a low barrier to interconversion between the isomers, for example, the enol/imino forms for cytosine and guanine. Tautomerization is a process where the chemical structure of a molecule, such as DNA bases, undergoes a rearrangement of its atoms. This rearrangement results in the formation of different isomers, called tautomers, which can exist in solution or in a cell. The DNA bases can undergo tautomeric shifts, which can potentially contribute to mutagenic mispairings during DNA replication. The energy required for tautomerization of DNA bases is known as tautomerization energy. These values were taken from reference (2) and the value for each base corresponds to the average of the values estimated from different measurement approaches.

Usage

```
data("dna_phyche", package = "GenomAutomorphism")
```

Format

A data frame object.

References

1. Wolfram Research (2007), ChemicalData, Wolfram Language function, <https://reference.wolfram.com/language/ref/ChemicalData.html> (updated 2016).
2. Moser A, Range K, York DM. Accurate proton affinity and gas-phase basicity values for molecules important in biocatalysis. *J Phys Chem B*. 2010;114: 13911–13921. doi:10.1021/jp107450n.
3. Leo A, Hansch C, Elkins D. Partition coefficients and their uses. *Chem Rev*. 1971;71: 525–616. doi:10.1021/cr60274a001.
4. Vovusha H, Amorim RG, Scheicher RH, Sanyal B. Controlling the orientation of nucleobases by dipole moment interaction with graphene/h-BN interfaces. *RSC Adv. Royal Society of Chemistry*; 2018;8: 6527–6531. doi:10.1039/c7ra11664k.

Examples

```
data("dna_phyche", package = "GenomAutomorphism")
dna_phyche

## Select DNA base tautomerization energy
te <- as.list(dna_phyche$tautomerization_energy)
names(te) <- rownames(dna_phyche)

## Let's create DNAStringSet-class object
base <- DNAStringSet(x = c( seq1 = 'ACGTGATCAAGT',
                           seq2 = 'GTGTGATCCAGT'))

dna_phychem(seqs = base, phychem = te,
            index_name = "Tautomerization-Energy")
```

dna_phychem

DNA numerical matrix

Description

This function applies the numerical indices representing various physicochemical and biochemical properties of DNA bases. As results, DNA sequences are represented as numerical vectors which can be subject of further downstream statistical analysis and digital signal processing.

Usage

```
dna_phychem(seqs, ...)

## S4 method for signature 'character'
dna_phychem(
  seqs,
  phychem = list(A = NULL, T = NULL, C = NULL, G = NULL, N = NULL)
)
```

```
## S4 method for signature 'DNASet_OR_DNAMultipleAlignment'
dna_phychem(
  seqs,
  phychem = list(A = NULL, T = NULL, C = NULL, G = NULL, N = NULL),
  index_name = NULL,
  ...
)
```

Arguments

<code>seqs</code>	A character string, a DNASet or a DNAMultipleAlignment class object carrying the DNA pairwise alignment of two sequences.
<code>...</code>	Not in use.
<code>phychem</code>	A list of DNA bases physicochemical properties, e.g., like those provided in dna_phyche .
<code>index_name</code>	Optional. Name of breve description of the base physicochemical property applied to represent the DNA sequence.

Value

A [MatrixSeq](#)-class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[peptide_phychem_index](#)

Examples

```
## Let's create DNASet-class object
base <- DNASet(x = c( seq1 = 'ACGTGATCAAGT',
                      seq2 = 'GTGTGATCCAGT',
                      seq3 = 'TCCTGATCAGGT'))

dna_phychem(seqs = base,
  phychem = list('A' = 0.87, 'C' = 0.88, 'T' = 0.82,
                 'G' = 0.89, 'N' = NA),
  index_name = "Proton-Affinity")
```

Description

This is a R package to compute the automorphisms between pairwise aligned DNA sequences represented as elements from a Genomic Abelian group as described in reference (1). In a general scenario, whole chromosomes or genomic regions from a population (from any species or close related species) can be algebraically represented as a direct sum of cyclic groups or more specifically Abelian p -groups. Basically, we propose the representation of multiple sequence alignments (MSA) of length N as a finite Abelian group created by the direct sum of homocyclic Abelian group of *prime-power order*.

Author(s)

Maintainer: Robersy Sanchez <genomicmath@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/genomaths/GenomAutomorphism>
- Report bugs at <https://github.com/genomaths/GenomAutomorphism/issues>

getAutomorphisms

Get Automorphisms

Description

For the sake of saving memory, each [Automorphism-class](#) objects is stored in an [AutomorphismList-class](#), which does not inherits from a [GRanges-class](#).

Usage

```
getAutomorphisms(x, ...)

## S4 method for signature 'AutomorphismList'
getAutomorphisms(x)

## S4 method for signature 'list'
getAutomorphisms(x)

## S4 method for signature 'DataFrame_OR_data.frame'
getAutomorphisms(x)
```

Arguments

x	An AutomorphismList-class .
...	Not in use.

Details

This function just transform each [Automorphism-class](#) object into an object from the same class but now inheriting from a [GRanges-class](#).

Value

This function returns an [AutomorphismList-class](#) object as a list of [Automorphism-class](#) objects, which inherits from [GRanges-class](#) objects.

An [AutomorphismList-class](#)

An [Automorphism-class](#)

Examples

```
## Load a dataset
data("autm", package = "GenomAutomorphism")
aut <- mcols(autm)
aut ## This a DataFrame object

## The natural ranges for the sequence (from 1 to length(aut)) are added
getAutomorphisms(aut)

## A list of automorphisms
aut <- list(aut, aut)
getAutomorphisms(aut)

## Automorphism-class inherits from 'GRanges-class'
aut <- as(autm, "GRanges")
as(aut, "Automorphism")
```

get_coord	<i>DNA base/codon sequence and coordinates represented on a given Abelian group.</i>
-----------	--

Description

Given a string denoting a codon or base from the DNA (or RNA) alphabet and a genetic-code Abelian group as given in reference (1), this function returns an object from [CodonGroup-class](#) carrying the DNA base/codon sequence and coordinates represented on the given Abelian group.

Usage

```
get_coord(x, ...)

## S4 method for signature 'BaseGroup_OR_CodonGroup'
get_coord(x, output = c("all", "matrix.list"))

## S4 method for signature 'DNAStringSet_OR_NULL'
get_coord(
  x,
  output = c("all", "matrix.list"),
  base_seq = TRUE,
  filepath = NULL,
  cube = "ACGT",
  group = "Z4",
  start = NA,
  end = NA,
```

```
chr = 1L,
strand = "+"
)
```

Arguments

<code>x</code>	An object from a BaseGroup-class , CodonGroup-class , DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences. Objects from BaseGroup-class and CodonGroup-class are generated with functions: base_coord and codon_coord , respectively.
<code>...</code>	Not in use.
<code>output</code>	See 'Value' section.
<code>base_seq</code>	Logical. Whether to return the base or codon coordinates on the selected Abelian group. If codon coordinates are requested, then the number of the DNA bases in the given sequences must be multiple of 3.
<code>filepath</code>	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
<code>cube</code>	A character string denoting one of the 24 Genetic-code cubes, as given in references (2 2 3).
<code>group</code>	A character string denoting the group representation for the given base or codon as shown in reference (1).
<code>start, end, chr, strand</code>	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.

Details

Symbols '-' and 'N' usually found in DNA sequence alignments to denote gaps and missing/unknown bases are represented by the number: '-1' on Z4 and '0' in Z5. In Z64 the symbol 'NA' will be returned for codons including symbols '-' and 'N'.

Although the [CodonGroup-class](#) object returned by functions [codon_coord](#) and [base_coord](#) are useful to store genomic information, the base and codon coordinates are not given on them as numeric magnitudes. Function [get_coord](#) provides the way to get the coordinates in a numeric object in object from and still to preserve the base/codon sequence information.

Value

An object from [CodonGroup-class](#) class is returned when *output* = 'all'. This has two slots, the first one carrying a list of matrices and the second one carrying the codon/base sequence information. That is, if *x* is an object from [CodonGroup-class](#) class, then a list of matrices of codon coordinate can be retrieved as *x*@CoordList and the information on the codon sequence as *x*@SeqRanges. if *output* = 'matrix.list', then an object from [MatrixList](#) class is returned.

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## DNA base representation in the Abelian group Z5
coord <- get_coord(
```

```

    x = aln,
    cube = "ACGT",
    group = "Z5"
)
coord ## A list of vectors

## Extract the coordinate list
coordList(coord)

## Extract the sequence list
seqRanges(coord)

## DNA codon representation in the Abelian group Z64
coord <- get_coord(
  x = aln,
  base_seq = FALSE,
  cube = "ACGT",
  group = "Z64"
)
coord

## Extract the coordinate list
coordList(coord)

## Extract the sequence list
seqRanges(coord)

```

get_mutscore

Get Mutation Score from an AAindex or a Mutation/Distance Matrix

Description

This function is applied to get the mutation or contact potential scores representing the similarity/distance between amino acids corresponding to substitution mutations. The scores are retrieved from a mutation matrix or a statistical protein contact potentials matrix from [AAindex](#) (ver.9.2).

Alternatively, the mutation scores can be estimated based on an user mutation matrix, for example, see [aminoacid_dist](#) and [codon_dist_matrix](#).

Usage

```

get_mutscore(aa1, aa2, ...)

## S4 method for signature 'character,character'
get_mutscore(
  aa1,
  aa2,
  acc = NULL,
  aaindex = NULL,
  mutmat = NULL,
  alphabet = c("AA", "DNA"),
  num.cores = 1L,
  tasks = 0L,

```

```

    verbose = FALSE,
    ...
)

## S4 method for signature 'BaseSeq,missing'
get_mutscore(
  aa1,
  aa2,
  acc = NULL,
  aaindex = NULL,
  mutmat = NULL,
  alphabet = c("AA", "DNA"),
  stat = mean,
  numcores = 1L,
  num.cores = 1L,
  tasks = 0L,
  output = c("dist", "matrix", "vector"),
  na.rm = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'DNASTringSet,missing'
get_mutscore(
  aa1,
  aa2,
  acc = NULL,
  aaindex = NULL,
  mutmat = NULL,
  alphabet = c("AA", "DNA"),
  stat = mean,
  num.cores = 1L,
  tasks = 0L,
  verbose = TRUE,
  output = c("dist", "matrix", "vector"),
  na.rm = TRUE,
  ...
)

## S4 method for signature 'DNAMultipleAlignment,missing'
get_mutscore(
  aa1,
  aa2,
  acc = NULL,
  aaindex = NULL,
  mutmat = NULL,
  alphabet = c("AA", "DNA"),
  stat = mean,
  num.cores = 1L,
  tasks = 0L,
  verbose = TRUE,
  output = c("dist", "matrix", "vector"),

```



```

    na.rm = TRUE,
    ...
)

```

Arguments

aa1, aa2	A simple character representing an amino acids or a character string of letter from the amino acid alphabet or base-triplets from the DNA/RNA alphabet. If aa1 is an object from any of the classes: BaseSeq , DNAStrngSet , or DNAMultipleAlignment , then argument aa2 is not required.
...	Not in use.
acc	Accession id for a specified mutation or contact potential matrix.
aaindex	Database where the requested accession id is locate. The possible values are: "aaindex2" or "aaindex3".
mutmat	A mutation or any score matrix provided by the user.
alphabet	Whether the alphabet is from the 20 amino acid (AA) or four (DNA)/RNA base alphabet. This would prevent mistakes, i.e., the strings "ACG" would be a base-triplet on the DNA alphabet or simply the amino acid sequence of alanine, cysteine, and glutamic acid.
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	Optional. Only if num.cores > 1. If TRUE, prints the function log to stdout.
stat	Statistic that will be used to summarize the scores of the DNA sequences provided. Only if aa1 is an object from any of the classes: BaseSeq , DNAStrngSet , or DNAMultipleAlignment .
numcores	An integer to setup the number of parallel workers via makeCluster .
output	Optional. Class of the returned object. Only if aa1 is an object from any of the classes: BaseSeq , DNAStrngSet , or DNAMultipleAlignment .
na.rm	a logical evaluating to TRUE or FALSE indicating whether NA values should be stripped before the computation proceeds.

Details

If a score matrix is provided by the user, then it must be a symmetric matrix 20x20.

Value

A single numeric score or a numerical vector, or if **aa1** is an object from any of the classes: [BaseSeq](#), [DNAStrngSet](#), or [DNAMultipleAlignment](#), then depending on the user selection the returned object will be:

1. A lower diagonal numerical vector of the sequence pairwise scores.
2. A [dist](#)-class object.
3. A whole score matrix.

Author(s)

Robersy Sanchez <https://genomaths.com>

See Also

[aa_mutmat](#), [aaindex2](#) and [aaindex3](#).

Examples

```
## A single amino acids substitution mutation
get_mutscore("A", "C", acc = "MIYS930101", aaindex = "aaindex2")

## A tri-peptide mutation
get_mutscore(aa1 = "ACG", aa2 = "ATG", acc = "MIYS930101",
             aaindex = "aaindex2", alphabet = "AA")

## A single base-triple mutation, i.e., a single amino acid substitution
## mutation
get_mutscore(aa1 = "ACG", aa2 = "CTA", acc = "MIYS930101",
             aaindex = "aaindex2", alphabet = "DNA")

## Peptides can be also written as:
get_mutscore(aa1 = c("A", "C", "G"), aa2 = c("C", "T", "A"),
             acc = "MIYS930101", aaindex = "aaindex2", alphabet = "AA")
```

GRangesMatrixSeq-class

Definition of GRangesMatrixSeq-class

Description

This is a very simple flexible class to store DNA and aminoacid aligned sequences together with their physicochemical properties. That is, a place where each aminoacid or codon from the sequence is represented by numerical value from a physicochemical index.

Constructor for 'GRangesMatrixSeq-class' object.

Usage

```
GRangesMatrixSeq(
  object = NULL,
  seqnames = Rle(factor()),
  start = integer(0),
  end = integer(0),
  ranges = IRanges(),
  strands = Rle(strand()),
  elementMetadata = DataFrame(),
  seqinfo = NULL,
  seqs = character(),
  names = character(),
  aaindex = character(),
  phychem = character(),
  accession = character()
)
```

Arguments

object If provided, it must be a GRangesMatrixSeq-class object and in this case
 seqnames, start, end, ranges, strand, elementMetadata, seqinfo
 The same as in [GRanges](#)
 seqs, names, aaindex, phychem, accession
 The same as in [MatrixSeq](#).

Details

This is a convenient function to transform a [MatrixSeq](#)-class object returned by function [aa_phychem_index](#) into a 'GRangesMatrixSeq-class' object. Since a 'GRangesMatrixSeq-class' inherits from [GRanges-class](#), this transformation permits the application of several methods from GenomicRanges package in the downstream analysis.

Value

Given the slot values, it defines a MatrixList-class.
 Only used to specify signature in the S4 setMethod.

Examples

```
aln <- c(S1 = "ATGCGGATTAGA", S2 = "ATGACGATCACA",
        S3 = "ATGAGATCACAG")
cd <- DNAMultipleAlignment(aln)
r1 <- peptide_phychem_index(unmasked(cd), acc = "EISD840101")

r2 <- GRangesMatrixSeq(r1)
r2

slot(r2, "phychem")
```

GRanges_OR_NULL-class *A definition for the union of 'GRanges' and 'NULL' class.*

Description

A definition for the union of 'GRanges' and 'NULL' class.

is.url	<i>Check URLs</i>
--------	-------------------

Description

Check URLs

Usage

```
is.url(x)
```

Details

Internal use only.

Value

Logical values

ListCodonMatrix-class *A Convenient Class to Store Codon Coordinates in given Genetic Code cube.*

Description

ListCodonMatrix-class objects are generated by function [codon_matrix](#).

Usage

```
ListCodonMatrix(object, cube, group, seq_alias = NULL, names = NULL)
```

```
valid.ListCodonMatrix(x)
```

Arguments

object	A list of CodonMatrix-class objects
x	A 'ListCodonMatrix-class' object

Examples

```
## ListCodonMatrix-class objects are generated by function 'codon_matrix'.
## Let's create DNASTringSet-class object
base <- DNASTringSet(x = c( seq1 = 'ACGTGATCAAGT',
                           seq2 = 'GTGTGATCCAGT',
                           seq3 = 'TCCTGATCAGGT'))

x1 <- codon_matrix(base)
x1

## Extract the first element
x1[1]
x1$codon.1
x1[[1]]
```

matrices	<i>Get the Coordinate Representation from DNA Sequences on Specified Abelian Group</i>
----------	--

Description

Extract the Coordinate Representation from DNA Sequences on Specified Abelian Group.

Usage

```
matrices(x, ...)

## S4 method for signature 'MatrixList'
matrices(x)

## S4 method for signature 'CodonSeq'
matrices(x)

## S4 method for signature 'DNAStrngSet_OR_NULL'
matrices(
  x,
  base_seq = TRUE,
  filepath = NULL,
  cube = "ACGT",
  group = c("Z4", "Z5", "Z64", "Z125", "Z4^3", "Z5^3"),
  start = NA,
  end = NA,
  chr = 1L,
  strand = "+"
)
```

Arguments

x	An object from a DNAStrngSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences.
...	Not in use.
base_seq	Logical. Whether to return the base or codon coordinates on the selected Abelian group. If codon coordinates are requested, then the number of the DNA bases in the given sequences must be multiple of 3.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon & base</i> arguments are not provided.
cube	A character string denoting one of the 24 Genetic-code cubes, as given in references (2-3).
group	A character string denoting the group representation for the given base or codon as shown in reference (1).
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.

Details

These are alternative ways to get the list of matrices of base/codon coordinate and the information on the codon sequence from `CodonSeq` and `MatrixList` class objects. These functions can either take the output from functions `base_coord` and `matrices` or to operate directly on a `DNAStringSet` or to retrieve the a DNA sequence alignment from a file.

`base_seq` parameter will determine whether to return the matrices of coordinate for a DNA or codon sequence. While in function `seqranges`, `granges` parameter will determine whether to return a `GRanges-class` object or a `DataFrame`.

Value

The a list of vectors (group = c("Z4", "Z5", "Z64", "Z125")) or a list of matrices (group = ("Z4^3", "Z5^3")) carrying the coordinate representation on the specified Abelian group.

Author(s)

Roberly Sanchez <https://genomaths.com>

References

1. Roberly Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. doi: [10.1101/2021.06.01.446543](https://doi.org/10.1101/2021.06.01.446543)
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152.[PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560.

See Also

[Symmetric Group of the Genetic-Code Cubes](#).

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## Coordinate representation of the aligned sequences on "Z4".
## A list of vectors
matrices(
  x = aln,
  base_seq = TRUE,
  filepath = NULL,
  cube = "ACGT",
  group = "Z4",
)

## Coordinate representation of the aligned sequences on "Z4".
## A list of matrices
matrices(
  x = aln,
  base_seq = FALSE,
  filepath = NULL,
```

```

    cube = "ACGT",
    group = "Z5^3",
)

```

MatrixList-class	<i>Definition of MatrixList-class</i>
------------------	---------------------------------------

Description

A class denoting a list of matrices.

Value

Given the slot values, it defines a MatrixList-class.

MatrixSeq-class	<i>Definition of MatrixSeq-class</i>
-----------------	--------------------------------------

Description

This is a very simple flexible class to store DNA and aminoacid aligned sequences together with their physicochemical properties. That is, a place where each aminoacid or codon from the sequence is represented by numerical value from a physicochemical index.

Usage

```
MatrixSeq(seqs, matrix, names, aaindex, phychem, accession)
```

```
## S4 method for signature 'MatrixSeq'
show(object)
```

Arguments

seqs, matrix, names, aaindex, phychem, accession	See detail section
object	An object from 'MatrixSeq' class

Details

seqs: A string character vector of DNA or aminoacid sequences.

matrix: A numerical matrix or a numerical vector (in the constructor) carrying the specified aminoacid physicochemical indices for aminoacid in the DNA or aminoacid sequence(s).

names: Alias/names/IDs DNA or aminoacid sequences.

aaindex: Aminoacid index database where the physicochemical index can be found.

phychem: Description of the physicochemical index applied to represent the DNA or aminoacid sequences.

accession: Accession number or ID of the applied physicochemical index in the database.

Value

Given the slot values, it defines a MatrixSeq-class.

A MatrixSeq-class object

Print/show of a MatrixSeq-class object.

Author(s)

Robersy Sanchez <https://genomaths.com>

Examples

```
aln <- c(S1 = "ATGCGGATTAGA", S2 = "ATGACGATCACA", S3 = "ATGAGATCACAG")
cd <- DNAMultipleAlignment(aln)
r1 <- peptide_phychem_index(unmasked(cd), acc = "EISD840101")
r1

## Extract the second aminoacid sequence
r1[2]

## Using the sequence given name
r1$S1

## Extract the second aminoacid value from the first sequence
r1[1,2]

## Change the name the second sequence
names(r1) <- c('S1', 'Seq1', 'S1')
r1

## Extract the amino acid sequences
slot(r1, 'seqs')
```

mod	<i>Modulo Operation</i>
-----	-------------------------

Description

Integer remainder of the division of the integer n by m: $n \bmod m$.

Usage

```
mod(n, m, ...)
```

S4 method for signature 'matrix,numeric'

```
mod(n, m)
```

Arguments

n	A numeric vector (preferably of integers), a matrix where each element can be reduced to integers.
m	An integer vector (positive, zero, or negative).
...	Not in use.

Value

An element of x , an [Automorphism-class](#) object.

Author(s)

Robersy Sanchez (<https://genomaths.com>).

Examples

```
## Example 1
## Build a matrix 'n' and set a vector of integers 'm'
n <- diag(x=1, nrow = 4, ncol = 4) * c(43,125,2,112)
m <- c(64,4,4,64)

## Operation n mod m
mod(n = n, m = m)

## Or simply:
n %% m

## Example 2
m <- matrix(c(8,2,3, 11,12,13), nrow = 2)
m

m %% 4
```

modeq

A Wrapper Calling Modular Linear Equation Solver (MLE)

Description

It is just a wrapper function to call [modlin](#). This function is intended to be use internally. MLE ($a * x = b \bmod n$) not always has solution If the MLE has not solution the function will return the value -1. Also, if $a * x = b \bmod n$ has solution $x = 0$, then function 'modeq' will return -1.

Usage

```
modeq(a, b, n)
```

Value

A number. If the equation has not solution in their definition, domain it will return -1.

Examples

```
## The MLE  $10 * x = 3 \bmod 64$  has not solution
modeq(10, 3, 64)

## The result is the giving calling modlin(10, 4, 64)
modeq(10, 4, 64)
```

modlineq

*Modular System of Linear Equation Solver (MLE)***Description**

If a , b , and c are integer vectors, this function try to find, at each coordinate, the solution of the MLE $ax = b \bmod n$. If the MLE $ax = b \bmod n$ has not solutions (see [modlin](#)), the value reported for the coordinate will be 0 and the corresponding translation.

Usage

```
modlineq(a, b, n, no.sol = 0L)
```

Arguments

a	An integer or a vector of integers.
b	An integer or a vector of integers.
n	An integer or a vector of integers.
<code>no.sol</code>	Values to return when the equation is not solvable or yield the value 0. Default is 0.

Details

For a , b , and c integer scalars, it is just a wrapper function to call [modlin](#).

Value

If the solution is exact, then a numerical vector will be returned, otherwise, if there is not exact solution for some coordinate, the a list carrying the element on the diagonal matrix and a translation vector will be returned.

Examples

```
## Set the vector x, y, and m.
x <- c(9,32,24,56,60,27,28,5)
y <- c(8,1,0,56,60,0,28,2)
modulo <- c(64,125,64,64,64,64,64,64)

## Try to solve the modular equation a x = b mod n
m <- modlineq(a = x, b = y, n = modulo)
m

## Or in matrix form
diag(m)

## The reverse mapping is an affine transformation
mt <- modlineq(a = y, b = x, n = modulo, no.sol = 1L)
mt

## That is, vector 'x' is recovered with the transformaiton
(y %*% diag(mt$diag) + mt$translation) %% modulo
```

```
# Or
cat("\n---- \n")

(y %% diag(mt$diag) + mt$translation) %% modulo == x
```

mut_type

Classification of DNA base mutations

Description

Each DNA/RNA base can be classified into three main classes according to three criteria (1): number of hydrogen bonds (strong-weak), chemical type (purine-pyrimidine), and chemical groups (amino versus keto). Each criterion produces a partition of the set of bases: 1) According to the number of hydrogen bonds (on DNA/RNA double helix): strong $S = (C, G)$ (three hydrogen bonds) and weak $W = (A, U)$ (two hydrogen bonds). According to the chemical type: purines $R = (A, G)$ and pyrimidines $Y = (C, U)$. 3). According to the presence of amino or keto groups on the base rings: amino $M = (C, A)$ and keto $K = (G, U)$. So, each mutational event can be classified as according to the type of involved in it (2).

Usage

```
mut_type(x, y)
```

Arguments

x, y Character strings denoting DNA bases

Value

A character string of same length of 'x' and 'y'.

References

1. A. Cornish-Bowden, Nomenclature for incompletely specified bases in nucleic acid sequences: recommendations 1984, Nucleic Acids Res. 13 (1985) 3021-3030.
2. MA.A. Jimenez-Montano, C.R. de la Mora-Basanez, T. Poschel, The hypercube structure of the genetic code explains conservative and non-conservative aminoacid substitutions in vivo and in vitro, Biosystems. 39 (1996) 117-125.

Examples

```
## Mutation type 'R'
mut_type("A", "G")

## Mutation type 'M'
mut_type("A", "C")

## Mutation type 'W'
mut_type("A", "T")

## Mutation type 'S'
mut_type("G", "C")
```

peptide_phychem_index *Amino acid numerical matrix*

Description

This function applies numerical indices representing various physicochemical and biochemical properties of amino acids and pairs of amino acids to DNA protein-coding or to aminoacid sequences. As results, DNA protein-coding or the aminoacid sequences are represented as numerical vectors which can be subject of further downstream statistical analysis and digital signal processing.

Usage

```
peptide_phychem_index(aa, ...)

## S4 method for signature 'character'
peptide_phychem_index(
  aa,
  acc = NULL,
  aaindex = NA,
  userindex = NULL,
  alphabet = c("AA", "DNA"),
  genetic.code = getGeneticCode("1"),
  no.init.codon = FALSE,
  if.fuzzy.codon = "error",
  ...
)

## S4 method for signature 'DNAStrngSet_OR_DNAMultipleAlignment'
peptide_phychem_index(
  aa,
  acc = NULL,
  aaindex = NA,
  userindex = NULL,
  alphabet = c("AA", "DNA"),
  genetic.code = getGeneticCode("1"),
  no.init.codon = FALSE,
  if.fuzzy.codon = "error",
  num.cores = 1L,
  tasks = 0L,
  verbose = FALSE,
  ...
)
```

Arguments

aa	A character string, a DNAStrngSet or a DNAMultipleAlignment class object carrying the DNA pairwise alignment of two sequences.
...	Not in use.
acc	Accession id for a specified mutation or contact potential matrix.

aaindex	Database where the requested accession id is locate and from where the aminoacid indices can be obtained. The possible values are: "aaindex2" or "aaindex3".
userindex	User provided aminoacid indices. This can be a numerical vector or a matrix (20 x 20). If a numerical matrix is provided, then the aminoacid indices are computes as column averages.
alphabet	Whether the alphabet is from the 20 aminoacid (AA) or four (DNA)/RNA base alphabet. This would prevent mistakes, i.e., the strings "ACG" would be a base-triplet on the DNA alphabet or simply the amino acid sequence of alanine, cysteine, and glutamic acid.
genetic.code, no.init.codon, if.fuzzy.codon	The same as given in function translation .
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the function log to stdout.

Details

If a DNA sequence is given, then it is assumed that it is a DNA base-triplet sequence, i.e., the base sequence must be multiple of 3.

Errors can be originated if the given sequences carry letter which are not from the DNA or aminoacid alphabet.

Value

Depending on the user specifications, a mutation or contact potential matrix, a list of available matrices (indices) ids or index names can be returned. More specifically:

aa_mutmat: Returns an aminoacid mutation matrix or a statistical protein contact potentials matrix.

aa_index: Returns the specified aminoacid physicochemical indices.

Author(s)

Robersy Sanchez <https://genomaths.com>

Examples

```
## Let's create DNASTringSet-class object
base <- DNASTringSet(x = c( seq1 = 'ACGTCATAAAGT',
                           seq2 = 'GTGTAATACAGT',
                           seq3 = 'TCCTCATAAGGT'))

## The stop condon 'TAA' yields NA
aa <- peptide_phychem_index(base, acc = "EISD840101")
aa

## Description of the physicochemical index
slot(aa, 'phychem')

## Get the aminoacid sequences. The stop codon 'TAA' is replaced by '*'.

```

```
slot(aa, 'seqs')

aa <- peptide_phychem_index(base, acc = "MIYS850103", aaindex = "aaindex3")
aa

## Description of the physicochemical index
slot(aa, 'phychem')
```

reexports

Reexport useful functions to be available to users

Description

These objects are imported from other packages. Follow the links below to see their documentation.

BiocGenerics [end](#), [end<-](#), [start](#), [start<-](#), [strand](#), [strand<-](#), [width](#)

Biostrings [AAMultipleAlignment](#), [AAStringSet](#), [DNAMultipleAlignment](#), [DNAStrngSet](#), [GENETIC_CODE_TABLE](#), [getGeneticCode](#), [readDNAMultipleAlignment](#), [translate](#), [unmasked](#)

GenomicRanges [GRangesList](#), [makeGRangesFromDataFrame](#)

matrixStats [colMeans2](#), [colSds](#), [colSums2](#), [colVars](#), [rowMeans2](#), [rowSds](#), [rowSums2](#), [rowVars](#)

numbers [modlin](#), [modq](#)

S4Vectors [mcols](#), [mcols<-](#), [setValidity2](#)

XVector [subseq](#)

Value

The same as in [mcols](#).

The same as in [mcols](#).

The same as in [setValidity2](#).

The same as in [DNAStrngSet](#).

The same as in [AAStringSet](#).

The same as in [readDNAMultipleAlignment](#).

The same as in [DNAMultipleAlignment](#).

The same as in [AAMultipleAlignment](#).

The same as in [subseq](#).

The same as in [translate](#).

The same as in [GENETIC_CODE_TABLE](#).

The same as in [getGeneticCode](#).

The same as in [unmasked](#).

The same as in [width](#).

The same as in [start](#).

The same as in [start](#).

The same as in [end](#).

The same as in [end](#).
 The same as in [strand](#).
 The same as in [strand](#).
 The same as in [GRangesList](#).
 The same as in [makeGRangesFromDataFrame](#).
 The same as in [modq](#).
 The same as in [modlin](#).
 The same as in [rowSums2](#).
 The same as in [colSums2](#).
 The same as in [colMeans2](#).
 The same as in [rowMeans2](#).
 The same as in [rowVars](#).
 The same as in [colVars](#).
 The same as in [colSds](#).
 The same as in [rowSds](#).

Examples

```
## Load an Automorphism object and take its metacolumns
data("autm", package = "GenomAutomorphism")
mcols(autm)
## See \code{\link[BiocGenerics]{start}}.

## Load an Automorphism object and get some 'end' coordinates
data("autm", package = "GenomAutomorphism")
end(autm[20:50])
```

seqranges	<i>Get DNA sequence Ranges and Coordinates representation on a given Abelian Group</i>
-----------	--

Description

Extract the gene ranges and coordinates from a pairwise alignment of codon/base sequences represented on a given Abelian group.

Usage

```
seqranges(x, ...)

## S4 method for signature 'CodonSeq'
seqranges(x, granges = TRUE)

## S4 method for signature 'DNAStringSet_OR_NULL'
seqranges(
  x,
  granges = TRUE,
```

```

base_seq = TRUE,
filepath = NULL,
start = NA,
end = NA,
chr = 1L,
strand = "+"
)

```

Arguments

x	An object from a DNAStringSet or DNAMultipleAlignment class carrying the DNA pairwise alignment of two sequences.
...	Not in use.
granges	Logical. Whether to return a GRanges-class object or a DataFrame .
base_seq	Logical. Whether to return the base or codon coordinates on the selected Abelian group. If codon coordinates are requested, then the number of the DNA bases in the given sequences must be multiple of 3.
filepath	A character vector containing the path to a file in fasta format to be read. This argument must be given if <i>codon</i> & <i>base</i> arguments are not provided.
start, end, chr, strand	Optional parameters required to build a GRanges-class . If not provided the default values given for the function definition will be used.

Details

This function provide an alternative way to get the codon coordinate and the information on the codon sequence from a [CodonSeq](#) class objects. The function can either take the output from functions [codon_coord](#) or to operate directly on a [DNAStringSet](#) or to retrieve the a DNA sequence alignment from a file.

Value

A [GRanges-class](#)

Author(s)

Robersy Sanchez <https://genomaths.com>

References

1. Robersy Sanchez, Jesus Barreto (2021) Genomic Abelian Finite Groups. [doi:10.1101/2021.06.01.446543](#)
2. M. V Jose, E.R. Morgado, R. Sanchez, T. Govezensky, The 24 possible algebraic representations of the standard genetic code in six or in three dimensions, Adv. Stud. Biol. 4 (2012) 119-152.[PDF](#).
3. R. Sanchez. Symmetric Group of the Genetic-Code Cubes. Effect of the Genetic-Code Architecture on the Evolutionary Process MATCH Commun. Math. Comput. Chem. 79 (2018) 527-560.

See Also

[matrices](#), [codon_coord](#), and [base_coord](#).

Examples

```
## Load a pairwise alignment
data("aln", package = "GenomAutomorphism")
aln

## A GRanges object carrying the aligned DNA sequence.
seqranges(
  x = aln,
  base_seq = TRUE,
  filepath = NULL,
)

## A GRanges object carrying the aligned codon sequence.
seqranges(
  x = aln,
  base_seq = FALSE,
  filepath = NULL,
)
```

show,CodonSeq-method *Show method for 'CodonSeq' class object*

Description

Show method for 'CodonSeq' class object
 Show method for 'ListCodonMatrix' class object
 Show method for 'MatrixList' class object

Usage

```
## S4 method for signature 'CodonSeq'
show(object)

## S4 method for signature 'ListCodonMatrix'
show(object)

## S4 method for signature 'MatrixList'
show(object)
```

Arguments

object An object from 'MatrixList' class

Value

Print/show of a ListCodonMatrix-class object.
 Print/show of a MatrixList-class object.

slapply

*Apply a function over a list-like object preserving its attributes***Description**

This function apply a function over a list-like object preserving its attributes and simplify (if requested) the list as [sapply](#) function does. **slapply** returns a list of the same length as 'x', each element of which is the result of applying FUN to the corresponding element of 'x'.

Usage

```
slapply(
  x,
  FUN,
  keep.attr = FALSE,
  class = NULL,
  simplify = TRUE,
  USE.NAMES = TRUE,
  ...
)
```

Arguments

x	A list-like or vector-like object.
FUN, ...	The same as described in lapply .
keep.attr	Logic. If TRUE, then the original attributes from 'x' are preserved in the returned list. Default is FALSE.
class	Name of the class to which the returned list belongs to. Default is NULL.
simplify, USE.NAMES	The same as described in sapply .

Value

Same as in `?base::lapply` if `keep.attr = FALSE`. Otherwise same values preserving original attributes from 'x'.

Author(s)

Robersy Sanchez (<https://genomaths.com>).

See Also

[lapply](#) and [sapply](#)

Examples

```
## Create a list
x <- list(a = seq(10), beta = exp(seq(-3, 3)),
  logic = c(TRUE, FALSE, FALSE, TRUE))
class(x) <- "nice"
```

```
## To compute the list mean for each list element using 'base::lapply'  
class(slapply(x, mean, simplify = FALSE))  
  
## Simply 'base::lapply' preserving attributes  
slapply(x, mean, keep.attr = TRUE, simplify = FALSE)  
  
## To preserve attributes and simplify  
slapply(x, mean, keep.attr = TRUE, simplify = TRUE)
```

sortByChromAndStart	Sorting GRanges-class objects
---------------------	---

Description

Sorts a [GRanges-class](#) objects by seqname (chromosome), start, and position.

Usage

```
sortByChromAndStart(x)
```

```
sortByChromAndEnd(x)
```

Arguments

x	GRanges object
---	----------------

Details

Objects that inherits from a [GRanges-class](#) can be sorted as well.

Value

[GRanges-class](#) object or from the original object class.

Examples

```
GR <- as(c("chr2:1-1", "chr1:1-1"), "GRanges")  
GR <- sortByChromAndStart(GR)
```

str2chr	<i>String to Character</i>
---------	----------------------------

Description

A simple function to transform a string into character vector.

Usage

```
str2chr(x, split = "", ...)
```

S4 method for signature 'character'

```
str2chr(x, split = "", ...)
```

S4 method for signature 'list'

```
str2chr(x, split = "", num.cores = 1L, tasks = 0L, verbose = FALSE, ...)
```

Arguments

x	A character string or a list/vector of character strings.
split	The same as in strsplit
...	Further parameters for strsplit .
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the function log to stdout.

Value

A character string

Author(s)

Robersy Sanchez <https://genomaths.com>

Examples

```
## A character string
str2chr("ATCAGCGGGATCTT")
```

```
## A list of character strings
str2chr(list(str1 = "ATCAGCGGGATCTT", str2 = "CTTCTTCGTCAGGC"))
```

str2dig*String to Digits*

Description

A simple function to transform a string of digits into a numeric vector.

Usage

```
str2dig(x, split = "", ...)  
  
## S4 method for signature 'character'  
str2dig(x, split = "", ...)  
  
## S4 method for signature 'list'  
str2dig(x, split = "", num.cores = 1L, tasks = 0L, verbose = FALSE, ...)
```

Arguments

x	A character string or a list/ of character strings of numeric/digit symbols.
split	The same as in strsplit
...	Further parameters for strsplit .
num.cores, tasks	Parameters for parallel computation using package BiocParallel-package : the number of cores to use, i.e. at most how many child processes will be run simultaneously (see bplapply and the number of tasks per job (only for Linux OS).
verbose	If TRUE, prints the function log to stdout.

Value

A integer vector or a list of integer vectors.

Author(s)

Robersy Sanchez <https://genomaths.com>

Examples

```
## A integer vector  
str2dig("12231456247")  
  
## A list of integer vectors  
str2dig(list(num1 = "12231456247", num2 = "521436897"))
```

translation

*Translation of DNA/RNA sequences***Description**

This function extends [translate](#) function to include letters that are frequently found in the DNA sequence databases to indicate missing information and are not part of the the DNA/RNA alphabet. Also, it is able to process sequences as just simple 'character' objects.

Usage

```
translation(x, ...)

## S4 method for signature 'character'
translation(
  x,
  genetic.code = getGeneticCode("1"),
  no.init.codon = FALSE,
  if.fuzzy.codon = "error"
)

## S4 method for signature 'BioString'
translation(
  x,
  genetic.code = getGeneticCode("1"),
  no.init.codon = FALSE,
  if.fuzzy.codon = "error"
)
```

Arguments

x	A character string or the same arguments given to function translate .
...	Not in use yet.
genetic.code	The same as in translate
no.init.codon, if.fuzzy.codon	Used only if 'x' is not a 'character' object. The same as in translate .

Details

If argument 'x' belong to any of the classes admitted by function [translate](#), then this function is called to make the translation.

Value

The translated amino acid sequence.

Author(s)

Robercy Sanchez <https://genomaths.com>

See Also[translate](#)**Examples**

```
## Load a small DNA sequence alingment
data("aln", package = "GenomAutomorphism")

translation(aln)

## Load a pairwise DNA sequence alingment of COVID-19 genomes
data("covid_aln", package = "GenomAutomorphism")

translation(covid_aln)
```

```
valid.Automorphism.mcols
```

Valid Automorphism mcols

Description

Valid Automorphism mcols

Valid Automorphism

Usage

```
valid.Automorphism.mcols(x)

valid.Automorphism(x)
```

Arguments

x A 'Automorphism object'

Value

An Error if the metacolumn does not have a valid format

An Error if the Automorphism-class object is not valid.

valid.AutomorphismByCoef
Valid AutomorphismByCoef mcols

Description

Valid AutomorphismByCoef mcols

Usage

valid.AutomorphismByCoef(x)

Arguments

x A 'AutomorphismByCoef object'

Value

An error if 'x' is not a valid AutomorphismByCoef.

valid.AutomorphismByCoefList
Valid AutomorphismByCoefList mcols

Description

Valid AutomorphismByCoefList mcols

Usage

valid.AutomorphismByCoefList(x)

Arguments

x A 'AutomorphismByCoefList object'

Value

An error if 'x' is not a valid AutomorphismByCoefList.

```
valid.AutomorphismList
```

Valid AutomorphismList mcols

Description

Valid AutomorphismList mcols

Usage

```
valid.AutomorphismList(x)
```

Arguments

x A 'AutomorphismList object'

Value

An error if 'x' is not a valid AutomorphismList class object.

```
valid.BaseGroup.elem
```

Valid BaseGroup mcols

Description

Valid BaseGroup mcols
 Valid 'BaseGroup' inheritance from 'GRanges' class
 Valid BaseGroup

Usage

```
valid.BaseGroup.elem(x)
```

```
valid.GRanges(x)
```

```
valid.BaseGroup(x)
```

Arguments

x A 'BaseGroup object'

Value

If valid return NULL
 If valid return NULL
 If valid return NULL

valid.CodonGroup.mcols	<i>Valid CodonGroup mcols</i>
------------------------	-------------------------------

Description

Valid CodonGroup mcols

Valid CodonGroup

Usage

valid.CodonGroup.mcols(x)

valid.CodonGroup(x)

Arguments

x	A 'CodonGroup object'
---	-----------------------

Value

If valid return NULL

If valid return NULL

valid.MatrixList	<i>Valid MatrixList</i>
------------------	-------------------------

Description

Valid MatrixList

Usage

valid.MatrixList(x)

Arguments

x	A 'MatrixList object'
---	-----------------------

Value

If valid return NULL

Only used to specify signature in the S4 setMethod.

[,AutomorphismList,ANY,ANY-method

An S4 class to extract elements for objects created with GenomAutomorphism package

Description

First and second level subsetting of 'x'. Extraction using names can be done as x\$name.

Usage

```
## S4 method for signature 'AutomorphismList,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ListCodonMatrix,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'MatrixSeq,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'AutomorphismList,ANY,ANY'
x[[i, j, ...]]

## S4 method for signature 'ListCodonMatrix,ANY,ANY'
x[[i, j, ...]]

## S4 method for signature 'AutomorphismList'
x$name

## S4 method for signature 'ListCodonMatrix'
names(x)

## S4 method for signature 'ListCodonMatrix'
x$name

## S4 method for signature 'MatrixSeq'
x$name

## S4 replacement method for signature 'MatrixSeq,ANY'
names(x) <- value
```

Arguments

x	An object from AutomorphismList , ListCodonMatrix , or MatrixSeq .
i, j, ...	As in Extract .
name	Element name in the list 'x'.
value	A character vector of up to the same length as x, or NULL.

Value

An object from [AutomorphismList](#), [ListCodonMatrix](#), or [MatrixSeq](#) class.

Author(s)

Robersy Sanchez <https://genomaths.com>
Robersy Sanchez (<https://genomaths.com>).

Examples

```
## Load automorphisms found BRCA1 primate genes
data("brca1_autm", package = "GenomAutomorphism")

## Extract AutomorphismList object with only one element
brca1_autm[1]

## Extract Automorphism object with only one element
brca1_autm[[3]]

## Extract Automorphism object using element name.
brca1_autm[["human_1.gorilla_1"]]
```

Index

* datasets

[aaindex1](#), [3](#)
[aaindex2](#), [4](#)
[aaindex3](#), [5](#)
[aln](#), [7](#)
[autby_coef](#), [13](#)
[autm](#), [14](#)
[autm_3d](#), [14](#)
[autm_z125](#), [15](#)
[brca1_aln](#), [38](#)
[brca1_aln2](#), [39](#)
[brca1_autm](#), [40](#)
[brca1_autm2](#), [40](#)
[cdm_z64](#), [41](#)
[covid_aln](#), [54](#)
[covid_autm](#), [55](#)
[cyc_aln](#), [55](#)
[cyc_autm](#), [56](#)
[dna_phyche](#), [57](#)

* internal

[\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[Automorphism-class](#), [16](#)
[AutomorphismByCoef-class](#), [16](#)
[AutomorphismByCoefList-class](#), [17](#)
[AutomorphismList-class](#), [19](#)
[base_repl](#), [38](#)
[BaseGroup-class](#), [33](#)
[BaseGroup_OR_CodonGroup-class](#), [33](#)
[BaseSeq-class](#), [34](#)
[BaseSeqMatrix-class](#), [34](#)
[CodonGroup-class](#), [41](#)
[CodonMatrix-class](#), [42](#)
[CodonSeq-class](#), [43](#)
[ConservedRegion-class](#), [52](#)
[GenomAutomorphism](#), [59](#)
[GRanges_OR_NULL-class](#), [67](#)
[GRangesMatrixSeq-class](#), [66](#)
[is.url](#), [67](#)
[ListCodonMatrix-class](#), [68](#)
[MatrixList-class](#), [71](#)
[MatrixSeq-class](#), [71](#)
[modeq](#), [73](#)

[reexports](#), [78](#)
[show, CodonSeq-method](#), [81](#)
[valid.Automorphism.mcols](#), [87](#)
[valid.AutomorphismByCoef](#), [88](#)
[valid.AutomorphismByCoefList](#), [88](#)
[valid.AutomorphismList](#), [89](#)
[valid.BaseGroup.elem](#), [89](#)
[valid.CodonGroup.mcols](#), [90](#)
[valid.MatrixList](#), [90](#)
'[\['](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
'[\[\['](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
'[%%'](#) (mod), [72](#)
'[names<-'](#) (AutomorphismList-class), [19](#)
[\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\[, ListCodonMatrix, ANY, ANY-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\[, MatrixSeq, ANY, ANY-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\[, AutomorphismList, ANY, ANY-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\[, ListCodonMatrix, ANY, ANY-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\\$\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\\$, AutomorphismList-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\\$, ListCodonMatrix-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)
[\\$, MatrixSeq-method\]](#)
[\(\[, AutomorphismList, ANY, ANY-method\]](#), [91](#)

[aa_index \(aa_phychem_index\)](#), [6](#)
[aa_mutmat](#), [5](#), [66](#)

- aa_mutmat (aa_phychem_index), 6
- aa_phychem_index, 6, 67
- aaindex1, 3, 5, 7
- aaindex2, 4, 4, 5, 7, 66
- aaindex3, 4, 5, 7, 66
- AAMultipleAlignment, 78
- AAMultipleAlignment (reexports), 78
- AAStringSet, 78
- AAStringSet (reexports), 78
- aln, 7
- aminoacid_dist, 8, 48, 63
- aminoacid_dist, AAStringSet, ANY-method (aminoacid_dist), 8
- aminoacid_dist, character, character-method (aminoacid_dist), 8
- aminoacid_dist, CodonGroup_OR_Automorphisms, ANY-method (aminoacid_dist), 8
- aminoacid_dist, DNASTringSet, ANY-method (aminoacid_dist), 8
- as.AutomorphismList, 10, 19
- as.AutomorphismList, GRangesList, GRanges_OR_NULL-method (as.AutomorphismList), 10
- as.AutomorphismList, list, GRanges_OR_NULL-method (as.AutomorphismList), 10
- as.list, AutomorphismList-method (AutomorphismList-class), 19
- aut3D, 11, 14
- autby_coef, 13
- autm, 14
- autm_3d, 14
- autm_z125, 15
- Automorphism (Automorphism-class), 16
- Automorphism-class, 16
- automorphism_bycoef, 11, 13, 16, 17, 22, 24
- automorphism_bycoef, Automorphism-method (automorphism_bycoef), 24
- automorphism_bycoef, AutomorphismList-method (automorphism_bycoef), 24
- AutomorphismByCoef, 23, 24, 53, 54
- AutomorphismByCoef (AutomorphismByCoef-class), 16
- AutomorphismByCoef-class, 16
- AutomorphismByCoefList, 13, 53
- AutomorphismByCoefList (AutomorphismByCoefList-class), 17
- AutomorphismByCoefList-class, 17
- automorphismByRanges, 18, 22
- automorphismByRanges, Automorphism-method (automorphismByRanges), 18
- automorphismByRanges, AutomorphismList-method (automorphismByRanges), 18
- AutomorphismList, 13–15, 40, 55, 56, 91
- AutomorphismList (AutomorphismList-class), 19
- AutomorphismList-class, 19
- automorphisms, 10, 11, 16, 18, 19, 21, 22, 24, 28, 33, 34, 41, 48
- automorphisms, DNASTringSet_OR_NULL-method (automorphisms), 21
- autZ125, 15, 25
- autZ5, 26
- autZ64, 14, 23, 28, 40, 55, 56
- base2codon, 30
- base2codon, character-method (base2codon), 30
- base2codon, DNAMultipleAlignment-method (base2codon), 30
- base2codon, DNASTringSet-method (base2codon), 30
- base2int, 31, 37, 45, 51
- base2int, character-method (base2int), 31
- base2int, data.frame-method (base2int), 31
- base_coord, 32, 34, 37, 42, 44, 45, 51, 62, 70, 80
- base_coord, DNASTringSet_OR_NULL-method (base_coord), 34
- base_matrix (base_coord), 34
- base_matrix, DNASTringSet_OR_NULL-method (base_coord), 34
- base_methods (base_coord), 34
- base_repl, 38
- base_seq2string_set (base_coord), 34
- base_seq2string_set, BaseSeq-method (base_coord), 34
- BaseGroup, 33, 36
- BaseGroup (BaseGroup-class), 33
- BaseGroup-class, 33
- BaseGroup_OR_CodonGroup (BaseGroup_OR_CodonGroup-class), 33
- BaseGroup_OR_CodonGroup-class, 33
- BaseSeq, 34, 65
- BaseSeq (BaseSeq-class), 34
- BaseSeq-class, 34
- BaseSeqMatrix, 50
- BaseSeqMatrix (BaseSeqMatrix-class), 34
- BaseSeqMatrix-class, 34
- bplapply, 9, 12, 18, 22, 24, 26, 27, 29, 47, 50, 53, 65, 77, 84, 85
- brca1_aln, 38, 39, 40, 54, 56
- brca1_aln2, 39, 39, 40, 56
- brca1_autm, 13, 39, 40, 55, 56

- brca1_autm2, [39](#), [40](#), [40](#), [54–56](#)
- cdm_z64, [41](#)
- codon_coord, [10](#), [32](#), [37](#), [42](#), [44](#), [48](#), [51](#), [62](#), [80](#)
- codon_coord, BaseGroup-method
(codon_coord), [44](#)
- codon_coord, DNASTringSet_OR_NULL-method
(codon_coord), [44](#)
- codon_coord, matrix_OR_data_frame-method
(codon_coord), [44](#)
- codon_dist, [9](#), [10](#), [46](#), [48](#), [49](#)
- codon_dist, character-method
(codon_dist), [46](#)
- codon_dist, CodonGroup_OR_Automorphisms-method
(codon_dist), [46](#)
- codon_dist, DNASTringSet-method
(codon_dist), [46](#)
- codon_dist_matrix, [41](#), [48](#), [48](#), [63](#)
- codon_matrix, [42](#), [45](#), [50](#), [68](#)
- codon_matrix, BaseSeqMatrix-method
(codon_matrix), [50](#)
- codon_matrix, DNAMultipleAlignment-method
(codon_matrix), [50](#)
- codon_matrix, DNASTringSet-method
(codon_matrix), [50](#)
- CodonGroup, [33](#)
- CodonGroup (CodonGroup-class), [41](#)
- CodonGroup-class, [41](#)
- CodonMatrix (CodonMatrix-class), [42](#)
- CodonMatrix-class, [42](#)
- CodonSeq, [70](#), [80](#)
- CodonSeq (CodonSeq-class), [43](#)
- CodonSeq-class, [43](#)
- colMeans2, [78](#), [79](#)
- colMeans2 (reexports), [78](#)
- colSds, [78](#), [79](#)
- colSds (reexports), [78](#)
- colSums2, [78](#), [79](#)
- colSums2 (reexports), [78](#)
- colVars, [78](#), [79](#)
- colVars (reexports), [78](#)
- conserved_regions, [23](#), [52](#)
- conserved_regions, Automorphism-method
(conserved_regions), [52](#)
- conserved_regions, AutomorphismByCoef-method
(conserved_regions), [52](#)
- conserved_regions, AutomorphismByCoefList-method
(conserved_regions), [52](#)
- conserved_regions, AutomorphismList-method
(conserved_regions), [52](#)
- ConservedRegion
(ConservedRegion-class), [52](#)
- ConservedRegion-class, [52](#)
- ConservedRegionList
(ConservedRegion-class), [52](#)
- ConservedRegionList-class
(ConservedRegion-class), [52](#)
- coordList (CodonSeq-class), [43](#)
- coordList, CodonSeq-method
(CodonSeq-class), [43](#)
- covid_aln, [14](#), [15](#), [39](#), [54](#), [54](#), [55](#), [56](#)
- covid_autm, [39](#), [40](#), [55](#), [56](#)
- cyc_aln, [39](#), [54](#), [55](#), [56](#)
- cyc_autm, [55](#), [56](#)
- data.frame, [16](#), [19](#)
- DataFrame, [11](#), [70](#), [80](#)
- DataFrame_OR_data.frame-class
(Automorphism-class), [16](#)
- dist, [65](#)
- dna_phyche, [57](#), [59](#)
- dna_phychem, [32](#), [58](#)
- dna_phychem, character-method
(dna_phychem), [58](#)
- dna_phychem, DNASTringSet_OR_DNAMultipleAlignment-method
(dna_phychem), [58](#)
- DNAMultipleAlignment, [12](#), [21](#), [25](#), [27](#), [29](#),
[35](#), [38](#), [39](#), [44](#), [50](#), [54–56](#), [59](#), [62](#), [65](#),
[69](#), [76](#), [78](#), [80](#)
- DNAMultipleAlignment (reexports), [78](#)
- DNASTringSet, [7](#), [12](#), [21](#), [25](#), [27](#), [29](#), [34](#), [35](#),
[44](#), [50](#), [59](#), [62](#), [65](#), [69](#), [70](#), [76](#), [78](#), [80](#)
- DNASTringSet (reexports), [78](#)
- DNASTringSet_OR_DNAMultipleAlignment-class
(GRangesMatrixSeq-class), [66](#)
- DNASTringSet_OR_NULL-class
(valid.MatrixList), [90](#)
- end, [78](#), [79](#)
- end (reexports), [78](#)
- end<- (reexports), [78](#)
- Extract, [91](#)
- extract
([, AutomorphismList, ANY, ANY-method),
[91](#)
- extract-methods
([, AutomorphismList, ANY, ANY-method),
[91](#)
- GENETIC_CODE_TABLE, [9](#), [12](#), [25](#), [29](#), [49](#), [78](#)
- GENETIC_CODE_TABLE (reexports), [78](#)
- GenomAutomorphism, [59](#)
- GenomAutomorphism-package
(GenomAutomorphism), [59](#)
- get_coord, [43](#), [61](#), [62](#)

- get_coord, BaseGroup_OR_CodonGroup-method (get_coord), 61
- get_coord, DNASTringSet_OR_NULL-method (get_coord), 61
- get_mutscore, 5, 7, 63
- get_mutscore, BaseSeq, missing-method (get_mutscore), 63
- get_mutscore, character, character-method (get_mutscore), 63
- get_mutscore, DNAMultipleAlignment, missing-method (get_mutscore), 63
- get_mutscore, DNASTringSet, missing-method (get_mutscore), 63
- getAutomorphisms, 23, 60
- getAutomorphisms, AutomorphismList-method (getAutomorphisms), 60
- getAutomorphisms, DataFrame_OR_data.frame-method (getAutomorphisms), 60
- getAutomorphisms, list-method (getAutomorphisms), 60
- getGeneticCode, 12, 25, 29, 78
- getGeneticCode (reexports), 78
- GRanges, 34, 67
- GRanges-class, 83
- GRanges_OR_NULL-class, 67
- GRangesList, 20, 78, 79
- GRangesList (reexports), 78
- GRangesMatrixSeq (GRangesMatrixSeq-class), 66
- GRangesMatrixSeq-class, 66
- is.url, 67
- lapply, 82
- ListCodonMatrix, 51, 91
- ListCodonMatrix (ListCodonMatrix-class), 68
- ListCodonMatrix-class, 68
- makeCluster, 49, 65
- makeGRangesFromDataFrame, 78, 79
- makeGRangesFromDataFrame (reexports), 78
- matrices, 69, 70, 80
- matrices, CodonSeq-method (matrices), 69
- matrices, DNASTringSet_OR_NULL-method (matrices), 69
- matrices, MatrixList-method (matrices), 69
- MatrixList, 62, 70
- MatrixList (MatrixList-class), 71
- MatrixList-class, 71
- MatrixSeq, 59, 67, 91
- MatrixSeq (MatrixSeq-class), 71
- MatrixSeq-class, 71
- mcols, 78
- mcols (reexports), 78
- mcols<- (reexports), 78
- mean, 9
- mod, 72
- mod, matrix, numeric-method (mod), 72
- modeq, 73
- modlin, 73, 74, 78, 79
- modlin (reexports), 78
- modlineq, 74
- modq, 78, 79
- modq (reexports), 78
- modulo (mod), 72
- MulticoreParam, 18, 24, 53
- mut_type, 24, 75
- names, AutomorphismList-method (AutomorphismList-class), 19
- names, ListCodonMatrix-method ([, AutomorphismList, ANY, ANY-method), 91
- names<-, AutomorphismList, ANY-method (AutomorphismList-class), 19
- names<-, MatrixSeq, ANY-method ([, AutomorphismList, ANY, ANY-method), 91
- peptide_phychem_index, 59, 76
- peptide_phychem_index, character-method (peptide_phychem_index), 76
- peptide_phychem_index, DNASTringSet_OR_DNAMultipleAlignment-method (peptide_phychem_index), 76
- readDNAMultipleAlignment, 78
- readDNAMultipleAlignment (reexports), 78
- reexports, 78
- rowMeans2, 78, 79
- rowMeans2 (reexports), 78
- rowSds, 78, 79
- rowSds (reexports), 78
- rowSums2, 78, 79
- rowSums2 (reexports), 78
- rowVars, 78, 79
- rowVars (reexports), 78
- sapply, 82
- scale, 32
- seq2granges (base_coord), 34
- seq2granges, DNASTringSet_OR_NULL-method (base_coord), 34
- seqRanges (CodonSeq-class), 43
- seqranges, 70, 79

- seqRanges, CodonSeq-method
(CodonSeq-class), 43
- seqranges, CodonSeq-method (seqranges),
79
- seqranges, DNASTringSet_OR_NULL-method
(seqranges), 79
- setValidity2, 78
- setValidity2 (reexports), 78
- show, AutomorphismList-method
(AutomorphismList-class), 19
- show, CodonSeq-method, 81
- show, ListCodonMatrix-method
(show, CodonSeq-method), 81
- show, MatrixList-method
(show, CodonSeq-method), 81
- show, MatrixSeq-method
(MatrixSeq-class), 71
- show-AutomorphismList
(AutomorphismList-class), 19
- show-CodonSeq (show, CodonSeq-method), 81
- show-ListCodonMatrix
(show, CodonSeq-method), 81
- show-MatrixList (show, CodonSeq-method),
81
- show-MatrixSeq (MatrixSeq-class), 71
- slapply, 82
- sortByChromAndEnd
(sortByChromAndStart), 83
- sortByChromAndStart, 83
- start, 78
- start (reexports), 78
- start<- (reexports), 78
- str2chr, 84
- str2chr, character-method (str2chr), 84
- str2chr, list-method (str2chr), 84
- str2dig, 85
- str2dig, character-method (str2dig), 85
- str2dig, list-method (str2dig), 85
- strand, 78, 79
- strand (reexports), 78
- strand<- (reexports), 78
- strsplit, 84, 85
- subseq, 78
- subseq (reexports), 78

- translate, 78, 86, 87
- translate (reexports), 78
- translation, 77, 86
- translation, BioString-method
(translation), 86
- translation, character-method
(translation), 86

- unmasked, 78
- unmasked (reexports), 78

- valid.Automorphism
(valid.Automorphism.mcols), 87
- valid.Automorphism.mcols, 87
- valid.AutomorphismByCoef, 88
- valid.AutomorphismByCoefList, 88
- valid.AutomorphismList, 89
- valid.BaseGroup (valid.BaseGroup.elem),
89
- valid.BaseGroup.elem, 89
- valid.CodonGroup
(valid.CodonGroup.mcols), 90
- valid.CodonGroup.mcols, 90
- valid.ConservedRegion
(ConservedRegion-class), 52
- valid.ConservedRegionList
(ConservedRegion-class), 52
- valid.GRanges (valid.BaseGroup.elem), 89
- valid.ListCodonMatrix
(ListCodonMatrix-class), 68
- valid.MatrixList, 90

- width, 78
- width (reexports), 78