

Package ‘Rbwa’

November 26, 2024

Version 1.10.0

Date 2023-06-29

Title R wrapper for BWA-backtrack and BWA-MEM aligners

Depends R (>= 4.1)

Suggests testthat, BiocStyle, knitr, rmarkdown

SystemRequirements GNU make

Description Provides an R wrapper for BWA alignment algorithms.

Both BWA-backtrack and BWA-MEM are available.

Convenience function to build a BWA index from a reference genome is also provided. Currently not supported for Windows machines.

License MIT + file LICENSE

URL <https://github.com/Jfortin1/Rbwa>

BugReports <https://github.com/crisprVerse/Rbwa/issues>

biocViews Sequencing, Alignment

VignetteBuilder knitr

RoxygenNote 7.1.2

OS_type unix

git_url <https://git.bioconductor.org/packages/Rbwa>

git_branch RELEASE_3_20

git_last_commit 82c4a0b

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-25

Author Jean-Philippe Fortin [aut, cre]

Maintainer Jean-Philippe Fortin <fortin946@gmail.com>

Contents

| | |
|---------------------------|---|
| bwa_aln | 2 |
| bwa_build_index | 3 |
| bwa_mem | 3 |
| bwa_sam | 4 |
| xa2multi | 6 |

Index**8**

| | |
|---------|--|
| bwa_aln | <i>R wrapper to run BWA alignment tool BWA-backtrack</i> |
|---------|--|

Description

R wrapper to run BWA alignment tool BWA-backtrack.

Usage

```
bwa_aln(
  type = c("single", "paired"),
  index_prefix,
  fastq_files,
  sai_files,
  ...
)
```

Arguments

| | |
|--------------|--|
| type | String specifying type of reads: "single" for single-end reads (default) or "paired" for paired-end reads. |
| index_prefix | String specifying prefix of the BWA index. |
| fastq_files | Character vector specifying paths of fastq files. If type=="single", must be of length 1. If type=="paired", must be of length 2. |
| sai_files | Character vector specifying filenames of the BWA alignment output files. If type=="single", must be of length 1. If type=="paired", must be of length 2. |
| ... | Other arguments to pass to the bwa aln alignment. |

Value

No return value. Output files from bwa aln alignment are produced as side effect.

Author(s)

Jean-Philippe Fortin

Examples

```
dir <- tempdir()
fasta <- system.file(package="Rbwa",
  "fasta/chr12.fa")
fastq <- system.file(package="Rbwa",
  "fastq/sequences.fastq")
index_prefix <- file.path(dir, "chr12")
bwa_build_index(fasta, index_prefix=index_prefix)

bwa_aln(index_prefix=index_prefix,
  fastq_files=fastq,
  sai_files=file.path(dir, "output.sai"))
```

| | |
|-----------------|--|
| bwa_build_index | <i>R wrapper to create BWA index files</i> |
|-----------------|--|

Description

R wrapper to create BWA index files from a FASTA file.

Usage

```
bwa_build_index(fasta, index_prefix = NULL, ...)
```

Arguments

| | |
|--------------|---|
| fasta | String specifying path to a FASTA file. |
| index_prefix | String specifying prefix of the output BWA index. |
| ... | Other arguments to pass to bwa index. |

Value

No return value. BWA index files are produced as a side-effect.

Author(s)

Jean-Philippe Fortin

Examples

```
dir <- tempdir()
fasta <- system.file(package="Rbwa",
                     "fasta/chr12.fa")
bwa_build_index(fasta,
                index_prefix=file.path(dir,"chr12"))
```

| | |
|---------|--|
| bwa_mem | <i>R wrapper to run BWA alignment tool BWA-MEM</i> |
|---------|--|

Description

R wrapper to run BWA alignment tool BWA-MEM.

Usage

```
bwa_mem(type = c("single", "paired"), index_prefix, fastq_files, sam_file, ...)
```

Arguments

| | |
|--------------|---|
| type | String specifying type of reads: "single" for single-end reads (default) or "paired" for paired-end reads. |
| index_prefix | String specifying prefix of the BWA index. |
| fastq_files | Character vector specifying paths of fastq files. If type=="single", must be of length 1. If type=="paired", must be of length 2. |
| sam_file | String specifying filename of the SAM alignment output. |
| ... | Other arguments to pass to the bwa aln alignment. |

Value

No return value. Output SAM file is produced as side effect.

Author(s)

Jean-Philippe Fortin

Examples

```
dir <- tempdir()
fasta <- system.file(package="Rbwa",
  "fasta/chr12.fa")
fastq <- system.file(package="Rbwa",
  "fastq/sequences.fastq")
index_prefix <- file.path(dir, "chr12")
bwa_build_index(fasta, index_prefix=index_prefix)

bwa_mem(index_prefix=index_prefix,
  fastq_files=fastq,
  sam_file=file.path(dir, "output.sam"))
```

bwa_sam

R wrapper to convert bwa aln output to SAM format

Description

R wrapper to convert bwa aln output to SAM format.

Usage

```
bwa_sam(
  type = c("single", "paired"),
  index_prefix,
  fastq_files,
  sai_files,
  sam_file,
  ...
)
```

Arguments

| | |
|--------------|--|
| type | String specifying type of reads: "single" for single-end reads (default) or "paired" for paired-end reads. |
| index_prefix | String specifying prefix of the BWA index. |
| fastq_files | Character vector specifying paths of fastq files. If type=="single", must be of length 1. If type=="paired", must be of length 2. |
| sai_files | Character vector specifying filenames of the bwa aln alignment output files. If type=="single", must be of length 1. If type=="paired", must be of length 2. |
| sam_file | String specifying paths of the SAM output file. |
| ... | Other arguments to pass to bwa_sam. |

Value

No return value. Output SAM files are produced as side effect.

Author(s)

Jean-Philippe Fortin

Examples

```
# Creating index:
dir <- tempdir()
fasta <- system.file(package="Rbwa",
                     "fasta/chr12.fa")
fastq <- system.file(package="Rbwa",
                     "fastq/sequences.fastq")
index_prefix <- file.path(dir, "chr12")
bwa_build_index(fasta, index_prefix=index_prefix)

# Creating alignments:
bwa_aln(index_prefix=index_prefix,
        fastq_files=fastq,
        sai_files=file.path(dir, "output.sai"))

# Generating SAM file:
bwa_sam(index_prefix=index_prefix,
        fastq_files=fastq,
        sai_files=file.path(dir, "output.sai"),
        sam_file=file.path(dir, "output.sam"))

# Reading in alignments from SAM file:
aln <- readLines(file.path(dir, "output.sam"))
aln
```

`xa2multi`*Unpack multiple alignments stored in BWA output*

Description

Unpack multiple alignments stored in BWA output

Usage

```
xa2multi(input_sam_file, output_sam_file)
```

Arguments

`input_sam_file` String specifying path of the input SAM file.
`output_sam_file`
String specifying path of the output SAM file.

Details

Each row in the SAM file produced by `bwa_aln` corresponds to the best alignment hit for a given input query sequence. Other alignments (secondary alignments, or other loci in case of multiple alignments) are stored in the XA tag.

`xa2multi` conveniently extracts the alignments from the XA tags and represent them as additional rows in the SAM format.

Value

Returns NULL invisibly. SAM file with multiple alignments is produced as a side effect.

Author(s)

Jean-Philippe Fortin

Examples

```
# Creating index:
dir <- tempdir()
fasta <- system.file(package="Rbwa",
                     "fasta/chr12.fa")
fastq <- system.file(package="Rbwa",
                     "fastq/sequences.fastq")
index_prefix <- file.path(dir, "chr12")
bwa_build_index(fasta, index_prefix=index_prefix)

# Creating alignments:
bwa_aln(index_prefix=index_prefix,
        fastq_files=fastq,
        sai_files=file.path(dir, "output.sai"))

# Generating SAM file:
bwa_sam(index_prefix=index_prefix,
        fastq_files=fastq,
        sai_files=file.path(dir, "output.sai"),
```

```
    sam_file=file.path(dir, "output.sam"))

# Generating multiple alignments:
xa2multi(input_sam_file=file.path(dir, "output.sam"),
         output_sam_file=file.path(dir, "output.multi.sam"))

#' Reading in:
aln <- readLines(file.path(dir, "output.multi.sam"))
aln
```

Index

bwa_aln, [2](#), [6](#)
bwa_build_index, [3](#)
bwa_mem, [3](#)
bwa_sam, [4](#)

xa2multi, [6](#)